

Package: FoReco (via r-universe)

October 11, 2026

Type Package

Title Forecast Reconciliation

Version 1.3.1.9000

Description Classical (bottom-up and top-down), optimal combination and heuristic point (Di Fonzo and Girolimetto, 2023 [doi:10.1016/j.ijforecast.2021.08.004](https://doi.org/10.1016/j.ijforecast.2021.08.004)) and probabilistic (Girolimetto et al. 2024 [doi:10.1016/j.ijforecast.2023.10.003](https://doi.org/10.1016/j.ijforecast.2023.10.003)) forecast reconciliation procedures for linearly constrained time series (e.g., hierarchical or grouped time series) in cross-sectional, temporal, or cross-temporal frameworks.

License GPL-3

URL <https://github.com/danigiro/FoReco>,
<https://danigiro.github.io/FoReco/>

BugReports <https://github.com/danigiro/FoReco/issues>

Depends R (>= 3.4), Matrix

Imports methods, osqp, stats, cli, distributional, lifecycle, generics

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

LazyData true

NeedsCompilation no

RoxygenNote 7.3.3

Roxygen list(markdown = TRUE)

Config/pak/sysreqs make

Repository <https://danigiro.r-universe.dev>

Date/Publication 2026-07-13 07:24:36 UTC

RemoteUrl <https://github.com/danigiro/foreco>

RemoteRef HEAD

RemoteSha f8c4f16f08de18e20753ee93bcdd17b9c109ca87

Contents

FoReco-package	3
aggs	3
balance_hierarchy	4
csboot	6
csbu	7
cscov	9
cslcc	10
csmo	14
csmvn	15
csprojmat	17
csrec	18
cssmp	21
cstd	23
cstools	24
ctboot	25
ctbu	27
ctcov	28
ctlcc	31
ctmo	34
ctmvn	36
ctprojmat	38
ctrec	39
ctsmmp	43
cttd	45
cttools	46
df2aggmat	47
foreco-class	49
itagdp	52
iterec	53
lcmat	54
set_bounds	56
shrink_estim	57
shrink_oasd	58
tcsrec	59
teboot	61
tebu	63
tecov	64
telcc	66
temo	69
temvn	70
teprojmat	72
terec	73
tesmp	77
tetd	78
tetools	79
unbalance_hierarchy	81

FoReco-package3

vndata 82

Index84

FoReco-package	<i>FoReco: Forecast Reconciliation</i>
----------------	--

Description

Classical (bottom-up and top-down), optimal combination and heuristic point (Di Fonzo and Girolimetto, 2023 [doi:10.1016/j.ijforecast.2021.08.004](#)) and probabilistic (Girolimetto et al. 2024 [doi:10.1016/j.ijforecast.2023.10.003](#)) forecast reconciliation procedures for linearly constrained time series (e.g., hierarchical or grouped time series) in cross-sectional, temporal, or cross-temporal frameworks.

Author(s)

Maintainer: Daniele Girolimetto <daniele.girolimetto@unipd.it> ([ORCID](#))

Authors:

- Tommaso Di Fonzo ([ORCID](#))

Other contributors:

- Yangzhuoran Fin Yang ([ORCID](#)) [contributor]

See Also

Useful links:

- <https://github.com/danigiuro/FoReco>
- <https://danigiuro.github.io/FoReco/>
- Report bugs at <https://github.com/danigiuro/FoReco/issues>

aggts	<i>Non-Overlapping Temporal Aggregation of a Time Series</i>
-------	--

Description

Non-overlapping temporal aggregation of a time series according to a specific aggregation order.

Usage

```
aggts(y, agg_order, tew = "sum", align = "end", rm_na = FALSE)
```

Arguments

<code>y</code>	Univariate or multivariate time series: a vector/matrix or a ts object.
<code>agg_order</code>	A numeric vector with the aggregation orders to consider.
<code>tew</code>	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
<code>align</code>	A string or a vector specifying the alignment of <code>y</code> . Options include: "end" (end of the series, <i>default</i>), "start" (start of the series), an integer (or a vector of integers) indicating the starting period of the temporally aggregated series.
<code>rm_na</code>	If TRUE the missing values are removed.

Value

A list of vectors or ts objects.

See Also

Utilities: [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [balance_hierarchy\(\)](#), [commat\(\)](#), [csprojmat\(\)](#), [cstools\(\)](#), [ctprojmat\(\)](#), [cttools\(\)](#), [df2aggmat\(\)](#), [lcmat\(\)](#), [res2matrix\(\)](#), [set_bounds\(\)](#), [shrink_estim\(\)](#), [shrink_oasd\(\)](#), [teprojmat\(\)](#), [tetools\(\)](#), [unbalance_hierarchy\(\)](#)

Examples

```
# Monthly time series (input vector)
y <- ts(rnorm(24), start = 2020, frequency = 12)
# Quarterly time series
x1 <- aggts(y, 3)
# Monthly, quarterly and annual time series
x2 <- aggts(y, c(1, 3, 12))
# All temporally aggregated time series
x3 <- aggts(y)

# Ragged data
y2 <- ts(rnorm(11), start = c(2020, 3), frequency = 4)
# Annual time series: start in 2021
x4 <- aggts(y2, 4, align = 3)
# Semi-annual (start in 2nd semester of 2020) and annual (start in 2021)
# time series
x5 <- aggts(y2, c(2, 4), align = c(1, 3))
```

Description

A hierarchy with L upper levels is said to be balanced if each variable at level l has at least one child at level $l + 1$. When this doesn't hold, the hierarchy is unbalanced. This function transforms an aggregation matrix of an unbalanced hierarchy into an aggregation matrix of a balanced one. This function is used to reconcile forecasts with [cslcc](#), which operates exclusively with balanced hierarchies.

Usage

```
balance_hierarchy(agg_mat, nodes = "auto", sparse = TRUE)
```

Arguments

agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
nodes	A $(L \times 1)$ numeric vector indicating the number of variables in each of the upper L levels of the hierarchy. The <i>default</i> value is the string "auto" which calculates the number of variables in each level.
sparse	Option to return sparse matrices (<i>default</i> is TRUE).

Value

A list containing four elements:

bam	The balanced aggregation matrix.
agg_mat	The input matrix.
nodes	A $(L \times 1)$ numeric vector indicating the number of variables in each of the L upper levels of the balanced hierarchy.
id	The identification number of each variable in the balanced hierarchy. It may contains duplicated values.

See Also

Utilities: [aggts\(\)](#), [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [commat\(\)](#), [csprojmat\(\)](#), [cstools\(\)](#), [ctprojmat\(\)](#), [cttools\(\)](#), [df2aggmat\(\)](#), [lcmat\(\)](#), [res2matrix\(\)](#), [set_bounds\(\)](#), [shrink_estim\(\)](#), [shrink_oasd\(\)](#), [teprojmat\(\)](#), [tetools\(\)](#), [unbalance_hierarchy\(\)](#)

Examples

```
#      Unbalanced      ->      Balanced
#      T                T
#      |-----|        |-----|
#      A         |        A         B
#      |---|      |        |---|      |
#      AA  AB  B      AA  AB  BA
A <- matrix(c(1, 1, 1,
              1, 1, 0), 2, byrow = TRUE)
obj <- balance_hierarchy(agg_mat = A, nodes = c(1, 1))
```

obj\$bam

csboot

Cross-sectional Joint Block Bootstrap

Description

Joint block bootstrap for generating probabilistic base forecasts that take into account the correlation between different time series (Panagiotelis et al. 2023).

Usage

```
csboot(model_list, boot_size, block_size, seed = NULL, xreg = NULL, ...)
```

Arguments

model_list	A list of all the n base forecasts models. A <code>simulate()</code> function for each model has to be available and implemented according to the package forecast , with the following mandatory parameters: <i>object</i> , <i>innov</i> , <i>future</i> , and <i>nsim</i> .
boot_size	The number of bootstrap replicates.
block_size	Block size of the bootstrap, which is typically equivalent to the forecast horizon.
seed	An integer seed.
xreg	An optional 3-d numeric array of dimensions $(\text{block_size} \times n \times N_{xreg})$ containing the new values of <i>xreg</i> to be used for forecasting. It can contain NAs.
...	Additional arguments for the <code>simulate()</code> function.

Value

A 3-d array ($\text{block_size} \times n \times \text{boot_size}$).

References

Panagiotelis, A., Gamakumara, P., Athanasopoulos, G. and Hyndman, R.J. (2023), Probabilistic forecast reconciliation: Properties, evaluation and score optimisation, *European Journal of Operational Research*, 306(2), 693–706. doi:[10.1016/j.ejor.2022.07.040](https://doi.org/10.1016/j.ejor.2022.07.040)

See Also

Bootstrap samples: [ctboot\(\)](#), [teboot\(\)](#)

Cross-sectional framework: [csbu\(\)](#), [cscov\(\)](#), [cslcc\(\)](#), [csmo\(\)](#), [csmvn\(\)](#), [csrec\(\)](#), [cssmp\(\)](#), [cstd\(\)](#), [cstools\(\)](#)

Examples

```
set.seed(123)

# Minimal example functions: each "model" stores Gaussian residuals;
# simulate() draws new innovations (innov=NULL) or uses the supplied ones
# (innov given).
simple_model <- function(res) {
  structure(list(residuals = res, sigma = sd(res)), class = "simple_model")
}
simulate.simple_model <- function(object, nsim = 1, innov = NULL,
                                future = TRUE, ...) {
  if (is.null(innov)) {
    rnorm(nsim, mean = 0, sd = object$sigma)
  } else {
    as.numeric(innov)[seq_len(nsim)]
  }
}

# Hierarchy Z = X + Y: 3 series, 50 in-sample residuals each
n <- 3
res <- matrix(rnorm(50 * n), nrow = 50, ncol = n)

# One model per cross-sectional series
model_list <- lapply(seq_len(n), function(i) simple_model(res[, i]))

# Joint block bootstrap: 100 replicates, forecast horizon h = 4
boot <- csboot(model_list = model_list, boot_size = 100, block_size = 4,
               seed = 1)
```

Description

This function computes the cross-sectional bottom-up reconciled forecasts (Dunn et al., 1976) for all series by appropriate summation of the bottom base forecasts $\hat{\mathbf{b}}$:

$$\tilde{\mathbf{y}} = \mathbf{S}_{cs} \hat{\mathbf{b}},$$

where $\mathbf{S}_{cs}$ is the cross-sectional structural matrix.

Usage

```
csbu(base, agg_mat, sntz = FALSE, round = FALSE)
```

Arguments

base	A ($h \times n_b$) numeric matrix or multivariate time series (mts class) containing bottom base forecasts; h is the forecast horizon, and n_b is the total number of bottom variables.
agg_mat	A ($n_a \times n_b$) numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
sntz	Logical. If TRUE, the negative base forecasts are set to zero (Di Fonzo and Girolimetto, 2023; Girolimetto 2025) before applying bottom-up. <i>Default</i> is FALSE.
round	Logical. If TRUE, base forecasts are rounded before applying the bottom-up reconciliation. <i>Default</i> is FALSE.

Value

An object of class `foreco` (see [foreco-class](#)) with a ($h \times n$) numeric matrix of cross-sectional reconciled forecasts.

References

- Dunn, D. M., Williams, W. H. and Dechaine, T. L. (1976), Aggregate versus subaggregate models in local area forecasting, *Journal of the American Statistical Association* 71(353), 68–71. [doi:10.1080/01621459.1976.10481478](#)
- Di Fonzo, T. and Girolimetto, D. (2023), Spatio-temporal reconciliation of solar forecasts, *Solar Energy*, 251, 13–29. [doi:10.1016/j.solener.2023.01.003](#)
- Girolimetto, D. (2025), Non-negative forecast reconciliation: Optimal methods and operational solutions. *Forecasting*, 7(4), 64; [doi:10.3390/forecast7040064](#)

See Also

Bottom-up reconciliation: [ctbu\(\)](#), [tebu\(\)](#)

Cross-sectional framework: [csboot\(\)](#), [cscov\(\)](#), [cslcc\(\)](#), [csmo\(\)](#), [csmvn\(\)](#), [csrec\(\)](#), [cssmp\(\)](#), [cstd\(\)](#), [cstools\(\)](#)

Examples

```
set.seed(123)
# (3 x 2) bottom base forecasts matrix (simulated), Z = X + Y
bts <- matrix(rnorm(6, mean = c(10, 10)), 3, byrow = TRUE)

# Aggregation matrix for Z = X + Y
A <- t(c(1,1))
reco <- csbu(base = bts, agg_mat = A)

# Non negative reconciliation
bts[2,2] <- -bts[2,2] # Making negative one of the base forecasts for Y
nnreco <- csbu(base = bts, agg_mat = A, sntz = TRUE)
```

cscov

*Cross-sectional Covariance Matrix Approximation***Description**

This function provides an approximation of the cross-sectional base forecasts errors covariance matrix using different reconciliation methods (see Wickramasuriya et al., 2019 and Di Fonzo and Girolimetto, 2023).

Usage

```
cscov(comb = "ols", agg_mat = NULL, res = NULL, n = NULL, mse = TRUE,
      shrink_fun = shrink_estim, ...)
```

Arguments

comb	A string specifying the covariance approximation method. • For ordinary least squares reconciliation: – "ols" (<i>default</i>) - identity error covariance matrix. • For weighted least squares reconciliation: – "str" - structural variances. – "wls" - series variances (uses res). • For generalized least squares (uses res) reconciliation: – "shr" - shrunk covariance (Wickramasuriya et al., 2019). – "oasd" - oracle shrunk covariance (Ando and Xiao, 2023). – "sam" - sample covariance. • Others (no for reconciliation): – "bu" - bottom-up covariance.
agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
res	An $(N \times n)$ optional numeric matrix containing the in-sample residuals or validation errors. This matrix is used to compute some covariance matrices.
n	Number of variables ($n = n_a + n_b$).
mse	If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected.
shrink_fun	Shrinkage function of the covariance matrix, shrink_estim (<i>default</i>).
...	Not used.

Value

A $(n \times n)$ symmetric positive (semi-)definite matrix.

References

- Ando, S., and Xiao, M. (2023), High-dimensional covariance matrix estimation: shrinkage toward a diagonal target. *IMF Working Papers*, 2023(257), A001.
- Di Fonzo, T. and Girolimetto, D. (2023a), Cross-temporal forecast reconciliation: Optimal combination method and heuristic alternatives, *International Journal of Forecasting*, 39, 1, 39-57. [doi:10.1016/j.ijforecast.2021.08.004](https://doi.org/10.1016/j.ijforecast.2021.08.004)
- Wickramasuriya, S.L., Athanasopoulos, G. and Hyndman, R.J. (2019), Optimal forecast reconciliation for hierarchical and grouped time series through trace minimization, *Journal of the American Statistical Association*, 114, 526, 804-819. [doi:10.1080/01621459.2018.1448825](https://doi.org/10.1080/01621459.2018.1448825)

See Also

Cross-sectional framework: [csboot\(\)](#), [csbu\(\)](#), [cslcc\(\)](#), [csmo\(\)](#), [csmvn\(\)](#), [csrec\(\)](#), [cssmp\(\)](#), [cstd\(\)](#), [cstools\(\)](#)

Examples

```
# Aggregation matrix for Z = X + Y
A <- t(c(1,1))
# (10 x 3) in-sample residuals matrix (simulated)
res <- t(matrix(rnorm(n = 30), nrow = 3))

cov1 <- cscov("ols", n = 3)          # OLS
cov2 <- cscov("str", agg_mat = A)    # STR
cov3 <- cscov("wls", res = res)      # WLS
cov4 <- cscov("shr", res = res)      # SHR
cov5 <- cscov("sam", res = res)      # SAM

# Custom covariance matrix
cscov.ols2 <- function(comb, x) diag(x)
cscov(comb = "ols2", x = 3) # == cscov("ols", n = 3)
```

cslcc

Level Conditional Coherent Reconciliation for Genuine Hierarchical/Grouped Time Series

Description

This function implements the cross-sectional forecast reconciliation procedure that extends the original proposal by Hollyman et al. (2021). Level conditional coherent reconciled forecasts are conditional on (i.e., constrained by) the base forecasts of a specific upper level in the hierarchy (exogenous constraints). It also allows handling the linear constraints linking the variables endogenously (Di Fonzo and Girolimetto, 2022). The function can calculate Combined Conditional Coherent (CCC) forecasts as simple averages of Level-Conditional Coherent (LCC) and bottom-up reconciled forecasts, with either endogenous or exogenous constraints.

Usage

```
cslcc(base, agg_mat, comb = "ols", res = NULL, approach = "proj", nn = NULL,
      settings = NULL, CCC = TRUE, const = "exogenous", bts = NULL, ...)
```

Arguments

- | | |
|----------|--|
| base | A $(h \times n)$ numeric matrix or multivariate time series (mts class) containing the base forecasts to be reconciled; h is the forecast horizon, and n is the total number of time series ($n = n_a + n_b$). |
| agg_mat | A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables. |
| comb | A string specifying the reconciliation method. For a complete list, see cscov . |
| res | An $(N \times n)$ optional numeric matrix containing the in-sample residuals or validation errors. This matrix is used to compute some covariance matrices. |
| approach | A string specifying the approach used to compute the reconciled forecasts. Options include: <ul style="list-style-type: none"> • "proj" (<i>default</i>): Projection approach according to Byron (1978, 1979). • "strc": Structural approach as proposed by Hyndman et al. (2011). • "proj_osqp": Numerical solution using osqp for projection approach. • "strc_osqp": Numerical solution using osqp for structural approach. |
| nn | A string specifying the algorithm to compute non-negative forecasts: <ul style="list-style-type: none"> • "osqp": quadratic programming optimization (osqp solver, Girolimetto 2025). • "bpv": block principal pivoting algorithm (Wickramasuriya et al., 2020). • "nfca": negative forecasts correction algorithm (Kourentzes and Athanassopoulos, 2021; Girolimetto 2025). • "nnic": iterative non-negative reconciliation with immutable constraints (Girolimetto 2025). • "sntz": heuristic "set-negative-to-zero" (Di Fonzo and Girolimetto, 2023; Girolimetto 2025). |
| settings | A list of control parameters. <ul style="list-style-type: none"> • nn = "osqp" An object of class osqpSettings specifying settings for the osqp solver. For details, refer to the osqp documentation (Stellato et al., 2020) • nn = "bpv" <ul style="list-style-type: none"> – ptype = "fixed": permutation method: "random" or "fixed" – par = 10: the number of full exchange rules that may be attempted – tol = sqrt(.Machine\$double.eps): the tolerance criteria – gtol = sqrt(.Machine\$double.eps): the gradient tolerance criteria – itmax = 100: the maximum number of algorithm iterations • nn = "nfca" and nn = "nnic" <ul style="list-style-type: none"> – tol = sqrt(.Machine\$double.eps): the tolerance criteria – itmax = 100: the maximum number of algorithm iterations |

	• <code>nn = "sntz"</code> – <code>type = "bu"</code>: the type of set-negative-to-zero heuristic: "bu" for bottom-up, "tdp" for top-down proportional, "tdsp" for top-down square proportional, "tdvw" for top-down variance weighted (the <code>res</code> param is used). See Girolimetto (2025) for details. – <code>tol = sqrt(.Machine\$double.eps)</code>: the tolerance identification of negative values
CCC	A logical value indicating whether the Combined Conditional Coherent reconciled forecasts reconciliation should include bottom-up forecasts (TRUE, <i>default</i>), or not.
const	A string specifying the reconciliation constraints: • "exogenous" (<i>default</i>): Fixes the top level of each sub-hierarchy. • "endogenous": Coherently revises both the top and bottom levels.
bts	A ($h \times n_b$) numeric matrix or multivariate time series (mts class) containing bottom base forecasts defined by the user (e.g., seasonal averages, as in Hollyman et al., 2021). This parameter can be omitted if only base forecasts are used (see Di Fonzo and Girolimetto, 2024).
...	Arguments passed on to <code>cscov</code>
	mse If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected.
	shrink_fun Shrinkage function of the covariance matrix, <code>shrink_estim</code> (<i>default</i>).

Value

An object of class `foreco` (see [foreco-class](#)) with a ($h \times n$) numeric matrix of cross-sectional reconciled forecasts.

References

- Byron, R.P. (1978), The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 141, 3, 359–367. doi:10.2307/2344807
- Byron, R.P. (1979), Corrigenda: The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 142(3), 405. doi:10.2307/2982515
- Di Fonzo, T. and Girolimetto, D. (2024), Forecast combination-based forecast reconciliation: Insights and extensions, *International Journal of Forecasting*, 40(2), 490–514. doi:10.1016/j.ijforecast.2022.07.001
- Di Fonzo, T. and Girolimetto, D. (2023b) Spatio-temporal reconciliation of solar forecasts. *Solar Energy* 251, 13–29. doi:10.1016/j.solener.2023.01.003
- Girolimetto, D. (2025), Non-negative forecast reconciliation: Optimal methods and operational solutions. *Forecasting*, 7(4), 64; doi:10.3390/forecast7040064
- Hyndman, R.J., Ahmed, R.A., Athanasopoulos, G. and Shang, H.L. (2011), Optimal combination forecasts for hierarchical time series, *Computational Statistics & Data Analysis*, 55, 9, 2579–2589. doi:10.1016/j.csda.2011.03.006
- Kourentzes, N. and Athanasopoulos, G. (2021) Elucidate structure in intermittent demand series. *European Journal of Operational Research*, 288, 141–152. doi:10.1016/j.ejor.2020.05.046

Hollyman, R., Petropoulos, F. and Tipping, M.E. (2021), Understanding forecast reconciliation. *European Journal of Operational Research*, 294, 149–160. doi:10.1016/j.ejor.2021.01.017

Stellato, B., Banjac, G., Goulart, P., Bemporad, A. and Boyd, S. (2020), OSQP: An Operator Splitting solver for Quadratic Programs, *Mathematical Programming Computation*, 12, 4, 637-672. doi:10.1007/s12532020001792

See Also

Level conditional coherent reconciliation: `ctlcc()`, `telcc()`

Cross-sectional framework: `csboot()`, `csbu()`, `cscov()`, `csmo()`, `csmvn()`, `csrec()`, `cssmp()`, `cstd()`, `cstools()`

Examples

```
set.seed(123)
# Aggregation matrix for Z = X + Y, X = XX + XY and Y = YX + YY
A <- matrix(c(1,1,1,1,1,1,0,0,0,0,1,1), 3, byrow = TRUE)
# (2 x 7) base forecasts matrix (simulated)
base <- matrix(rnorm(7*2, mean = c(40, 20, 20, 10, 10, 10, 10)), 2, byrow = TRUE)
# (10 x 7) in-sample residuals matrix (simulated)
res <- matrix(rnorm(n = 7*10), ncol = 7)
# (2 x 7) Naive bottom base forecasts matrix: all forecasts are set equal to 10
naive <- matrix(10, 2, 4)

## EXOGENOUS CONSTRAINTS (Hollyman et al., 2021)
# Level Conditional Coherent (LCC) reconciled forecasts
exo_LC <- cslcc(base = base, agg_mat = A, comb = "wls", bts = naive,
               res = res, CCC = FALSE)

# Combined Conditional Coherent (CCC) reconciled forecasts
exo_CCC <- cslcc(base = base, agg_mat = A, comb = "wls", bts = naive,
               res = res, CCC = TRUE)

# Results detailed by level:
# L-1: Level 1 immutable reconciled forecasts for the whole hierarchy
# L-2: Middle-Out reconciled forecasts
# L-3: Bottom-Up reconciled forecasts
info_exo <- summary(exo_CCC)
info_exo$lcc

## ENDOGENOUS CONSTRAINTS (Di Fonzo and Girolimetto, 2024)
# Level Conditional Coherent (LCC) reconciled forecasts
endo_LC <- cslcc(base = base, agg_mat = A, comb = "wls",
               res = res, CCC = FALSE,
               const = "endogenous")

# Combined Conditional Coherent (CCC) reconciled forecasts
endo_CCC <- cslcc(base = base, agg_mat = A, comb = "wls",
               res = res, CCC = TRUE,
               const = "endogenous")
```

```
# Results detailed by level:
# L-1: Level 1 reconciled forecasts for L1 + L3 (bottom level)
# L-2: Level 2 reconciled forecasts for L2 + L3 (bottom level)
# L-3: Bottom-Up reconciled forecasts
info_endo <- summary(endo_CCC)
info_endo$lcc
```

csmo

Cross-sectional Middle-out Reconciliation

Description

The middle-out forecast reconciliation (Athanasopoulos et al., 2009) combines top-down ([cstd](#)) and bottom-up ([csbu](#)) for genuine hierarchical/grouped time series. Given the base forecasts of variables at an intermediate level l , it performs

- a top-down approach for the levels $< l$;
- a bottom-up approach for the levels $> l$.

Usage

```
csmo(base, agg_mat, weights, id_rows = 1, normalize = TRUE)
```

Arguments

base	A $(h \times n_l)$ numeric matrix containing the l -level base forecast; n_l is the number of variables at level l , and h is the forecast horizon.
agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
weights	A $(h \times n_b)$ numeric matrix containing the proportions for the bottom time series; h is the forecast horizon, and n_b is the total number of bottom variables.
id_rows	A numeric vector indicating the l -level rows of <code>agg_mat</code> .
normalize	If TRUE (<i>default</i>), the weights will sum to 1.

Value

An object of class `foreco` (see [foreco-class](#)) with a $(h \times n)$ numeric matrix of cross-sectional reconciled forecasts.

References

Athanasopoulos, G., Ahmed, R. A. and Hyndman, R.J. (2009) Hierarchical forecasts for Australian domestic tourism. *International Journal of Forecasting* 25(1), 146–166. doi:[10.1016/j.ijforecast.2008.07.004](https://doi.org/10.1016/j.ijforecast.2008.07.004)

See Also

Middle-out reconciliation: `ctmo()`, `temo()`

Cross-sectional framework: `csboot()`, `csbu()`, `cscov()`, `cslcc()`, `csmvn()`, `csrec()`, `cssmp()`, `cstd()`, `cstools()`

Examples

```
set.seed(123)
# Aggregation matrix for  $Z = X + Y$ ,  $X = XX + XY$  and  $Y = YX + YY$ 
A <- matrix(c(1,1,1,1,1,1,0,0,0,0,1,1), 3, byrow = TRUE)
# (3 x 2) top base forecasts vector (simulated), forecast horizon = 3
baseL2 <- matrix(rnorm(2*3, 5), 3, 2)
# Same weights for different forecast horizons
fix_weights <- runif(4)
reco <- csmo(base = baseL2, agg_mat = A, id_rows = 2:3, weights = fix_weights)

# Different weights for different forecast horizons
h_weights <- matrix(runif(4*3), 3, 4)
recoh <- csmo(base = baseL2, agg_mat = A, id_rows = 2:3, weights = h_weights)
```

csmvn

*Cross-sectional Gaussian Probabilistic Reconciliation***Description**

This function performs cross-sectional probabilistic forecast reconciliation assuming a multivariate normal base forecast distribution (Panagiotelis et al., 2023; Girolimetto et al., 2024; Wickramasuriya, 2024) for linearly constrained (e.g. hierarchical or grouped) multiple time series.

Usage

```
csmvn(base, agg_mat, cons_mat, comb = "ols", res = NULL,
       approach = "proj", comb_base = comb, reduce_form = FALSE, ...)
```

Arguments

<code>base</code>	A $(h \times n)$ numeric matrix or multivariate time series (mts class) containing the base forecasts to be reconciled; h is the forecast horizon, and n is the total number of time series ($n = n_a + n_b$).
<code>agg_mat</code>	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
<code>cons_mat</code>	A $(n_a \times n)$ numeric matrix representing the cross-sectional zero constraints: each row represents a constraint equation, and each column represents a variable. The matrix can be of full rank, meaning the rows are linearly independent, but this is not a strict requirement, as the function allows for redundancy in the constraints.

comb	A string specifying the reconciliation method. For a complete list, see cscov .
res	An $(N \times n)$ optional numeric matrix containing the in-sample residuals or validation errors. This matrix is used to compute some covariance matrices.
approach	A string specifying the approach used to compute the reconciled mean and covariance matrix. Options include: • "proj" (<i>default</i>): Projection approach according to Byron (1978, 1979). • "strc": Structural approach as proposed by Hyndman et al. (2011).
comb_base	A string specifying the base covariance matrix approach. For a complete list, see cscov . Default is the equal to comb.
reduce_form	A logical parameter indicating whether the function should return the full distribution (FALSE, <i>default</i>) or only the distribution corresponding to the bottom-level time series (TRUE).
...	Arguments passed on to cscov
mse	If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected.
shrink_fun	Shrinkage function of the covariance matrix, shrink_estim (<i>default</i>).

Value

A [distributional::dist_multivariate_normal](#) of reconciled forecasts, of class `foreco` (see [foreco-class](#)).

References

- Byron, R.P. (1978), The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 141, 3, 359-367. [doi:10.2307/2344807](#)
- Byron, R.P. (1979), Corrigenda: The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 142(3), 405. [doi:10.2307/2982515](#)
- Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. [doi:10.1016/j.ijforecast.2023.10.003](#)
- Hyndman, R.J., Ahmed, R.A., Athanasopoulos, G. and Shang, H.L. (2011), Optimal combination forecasts for hierarchical time series, *Computational Statistics & Data Analysis*, 55, 9, 2579-2589. [doi:10.1016/j.csda.2011.03.006](#)
- Panagiotelis, A., Gamakumara, P., Athanasopoulos, G. and Hyndman, R.J. (2023), Probabilistic forecast reconciliation: Properties, evaluation and score optimisation, *European Journal of Operational Research* 306(2), 693–706. [doi:10.1016/j.ejor.2022.07.040](#)
- Wickramasuriya, S. L. (2024). Probabilistic Forecast Reconciliation under the Gaussian Framework. *Journal of Business & Economic Statistics*, 42(1), 272–285. [doi:10.1080/07350015.2023.2181176](#)

See Also

Probabilistic reconciliation: [cssmp\(\)](#), [ctmvn\(\)](#), [ctsmv\(\)](#), [temvn\(\)](#), [tesmv\(\)](#)

Cross-sectional framework: [csboot\(\)](#), [csbu\(\)](#), [cscov\(\)](#), [cslcc\(\)](#), [csmo\(\)](#), [csrec\(\)](#), [cssmp\(\)](#), [cstd\(\)](#), [cstools\(\)](#)

Examples

```
set.seed(123)
# (2 x 3) base forecasts matrix (simulated), Z = X + Y
base <- matrix(rnorm(6, mean = c(20, 10, 10)), 2, byrow = TRUE)
# (10 x 3) in-sample residuals matrix (simulated)
res <- t(matrix(rnorm(n = 30), nrow = 3))

# Aggregation matrix for Z = X + Y
A <- t(c(1,1))
reco_dist <- csmvn(base = base, agg_mat = A, comb = "shr", res = res)
```

csprojmat	<i>Projection Matrix for Optimal Combination Cross-sectional Reconciliation</i>
-----------	---

Description

This function computes the projection or the mapping matrix $\mathbf{M}$ and $\mathbf{G}$, respectively, such that $\tilde{\mathbf{y}} = \mathbf{M}\hat{\mathbf{y}} = \mathbf{S}_{cs}\mathbf{G}\hat{\mathbf{y}}$, where $\tilde{\mathbf{y}}$ is the vector of the reconciled forecasts, $\hat{\mathbf{y}}$ is the vector of the base forecasts, $\mathbf{S}_{cs}$ is the cross-sectional structural matrix, and $\mathbf{M} = \mathbf{S}_{cs}\mathbf{G}$. For further information regarding on the structure of these matrices, refer to Girolimetto et al. (2023).

Usage

```
csprojmat(agg_mat, cons_mat, comb = "ols", res = NULL, mat = "M", ...)
```

Arguments

agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
cons_mat	A $(n_a \times n)$ numeric matrix representing the cross-sectional zero constraints: each row represents a constraint equation, and each column represents a variable. The matrix can be of full rank, meaning the rows are linearly independent, but this is not a strict requirement, as the function allows for redundancy in the constraints.
comb	A string specifying the reconciliation method. For a complete list, see cscov .
res	An $(N \times n)$ optional numeric matrix containing the in-sample residuals or validation errors. This matrix is used to compute some covariance matrices.
mat	A string specifying which matrix to return: "M" (<i>default</i>) for $\mathbf{M}$ and "G" for $\mathbf{G}$.
...	Arguments passed on to cscov

mse If TRUE (*default*) the errors used to compute the covariance matrix are not mean-corrected.

shrink_fun Shrinkage function of the covariance matrix, [shrink_estim](#) (*default*).

Value

The projection matrix $\mathbf{M}$ (mat = "M") or the mapping matrix $\mathbf{G}$ (mat = "G").

References

Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. doi:[10.1016/j.ijforecast.2023.10.003](https://doi.org/10.1016/j.ijforecast.2023.10.003)

See Also

Utilities: [aggts\(\)](#), [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [balance_hierarchy\(\)](#), [commat\(\)](#), [cstools\(\)](#), [ctprojmat\(\)](#), [cttools\(\)](#), [df2aggmat\(\)](#), [lcmat\(\)](#), [res2matrix\(\)](#), [set_bounds\(\)](#), [shrink_estim\(\)](#), [shrink_oasd\(\)](#), [teprojmat\(\)](#), [tetools\(\)](#), [unbalance_hierarchy\(\)](#)

Examples

```
# Cross-sectional framework
A <- t(c(1,1)) # Aggregation matrix for Z = X + Y
Mcs <- csprojmat(agg_mat = A, comb = "ols")
Gcs <- csprojmat(agg_mat = A, comb = "ols", mat = "G")
```

csrec

Optimal Combination Cross-sectional Reconciliation

Description

This function performs optimal (in least squares sense) combination cross-sectional forecast reconciliation for a linearly constrained (e.g., hierarchical/grouped) multiple time series (Wickramasuriya et al., 2019, Panagiotelis et al., 2022, Girolimetto and Di Fonzo, 2023). The reconciled forecasts are calculated using either a projection approach (Byron, 1978, 1979) or the equivalent structural approach by Hyndman et al. (2011). Non-negative (Di Fonzo and Girolimetto, 2023) and immutable including Zhang et al., 2023) reconciled forecasts can be considered.

Usage

```
csrec(base, agg_mat, cons_mat, comb = "ols", res = NULL, approach = "proj",
      nn = NULL, settings = NULL, bounds = NULL, immutable = NULL, ...)
```

Arguments

base	A ($h \times n$) numeric matrix or multivariate time series (mts class) containing the base forecasts to be reconciled; h is the forecast horizon, and n is the total number of time series ($n = n_a + n_b$).
agg_mat	A ($n_a \times n_b$) numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.

cons_mat	A ($n_a \times n$) numeric matrix representing the cross-sectional zero constraints: each row represents a constraint equation, and each column represents a variable. The matrix can be of full rank, meaning the rows are linearly independent, but this is not a strict requirement, as the function allows for redundancy in the constraints.
comb	A string specifying the reconciliation method. For a complete list, see cscov .
res	An ($N \times n$) optional numeric matrix containing the in-sample residuals or validation errors. This matrix is used to compute some covariance matrices.
approach	A string specifying the approach used to compute the reconciled forecasts. Options include: • "proj" (<i>default</i>): Projection approach according to Byron (1978, 1979). • "strc": Structural approach as proposed by Hyndman et al. (2011). • "proj_osqp": Numerical solution using osqp for projection approach. • "strc_osqp": Numerical solution using osqp for structural approach.
nn	A string specifying the algorithm to compute non-negative forecasts: • "osqp": quadratic programming optimization (osqp solver, Girolimetto 2025). • "bpv": block principal pivoting algorithm (Wickramasuriya et al., 2020). • "nfca": negative forecasts correction algorithm (Kourentzes and Athanassopoulos, 2021; Girolimetto 2025). • "nnic": iterative non-negative reconciliation with immutable constraints (Girolimetto 2025). • "sntz": heuristic "set-negative-to-zero" (Di Fonzo and Girolimetto, 2023; Girolimetto 2025).
settings	A list of control parameters. • nn = "osqp" An object of class <code>osqpSettings</code> specifying settings for the osqp solver. For details, refer to the osqp documentation (Stellato et al., 2020) • nn = "bpv" – ptype = "fixed": permutation method: "random" or "fixed" – par = 10: the number of full exchange rules that may be attempted – tol = <code>sqrt(.Machine\$double.eps)</code>: the tolerance criteria – gtol = <code>sqrt(.Machine\$double.eps)</code>: the gradient tolerance criteria – itmax = 100: the maximum number of algorithm iterations • nn = "nfca" and nn = "nnic" – tol = <code>sqrt(.Machine\$double.eps)</code>: the tolerance criteria – itmax = 100: the maximum number of algorithm iterations • nn = "sntz" – type = "bu": the type of set-negative-to-zero heuristic: "bu" for bottom-up, "tdp" for top-down proportional, "tdsp" for top-down square proportional, "tdvw" for top-down variance weighted (the res param is used). See Girolimetto (2025) for details. – tol = <code>sqrt(.Machine\$double.eps)</code>: the tolerance identification of negative values

bounds	A matrix (see set_bounds) with 3 columns (i , <i>lower</i> , <i>upper</i>), such that • Column 1 represents the cross-sectional series ($i = 1, \dots, n$). • Columns 2 and 3 indicates the <i>lower</i> and <i>upper</i> bounds, respectively.
immutable	A numeric vector containing the column indices of the base forecasts (base parameter) that should be fixed.
...	Arguments passed on to cscov
mse	If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected.
shrink_fun	Shrinkage function of the covariance matrix, shrink_estim (<i>default</i>).

Value

An object of class `foreco` (see [foreco-class](#)) with a $(h \times n)$ numeric matrix of cross-sectional reconciled forecasts.

References

- Byron, R.P. (1978), The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 141, 3, 359-367. doi:[10.2307/2344807](#)
- Byron, R.P. (1979), Corrigenda: The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 142(3), 405. doi:[10.2307/2982515](#)
- Di Fonzo, T. and Girolimetto, D. (2023), Spatio-temporal reconciliation of solar forecasts, *Solar Energy*, 251, 13–29. doi:[10.1016/j.solener.2023.01.003](#)
- Girolimetto, D. (2025), Non-negative forecast reconciliation: Optimal methods and operational solutions. *Forecasting*, 7(4), 64; doi:[10.3390/forecast7040064](#)
- Girolimetto, D. and Di Fonzo, T. (2023), Point and probabilistic forecast reconciliation for general linearly constrained multiple time series, *Statistical Methods & Applications*, 33, 581-607. doi:[10.1007/s10260023007386](#).
- Hyndman, R.J., Ahmed, R.A., Athanasopoulos, G. and Shang, H.L. (2011), Optimal combination forecasts for hierarchical time series, *Computational Statistics & Data Analysis*, 55, 9, 2579-2589. doi:[10.1016/j.csda.2011.03.006](#)
- Kourentzes, N. and Athanasopoulos, G. (2021) Elucidate structure in intermittent demand series. *European Journal of Operational Research*, 288, 141-152. doi:[10.1016/j.ejor.2020.05.046](#)
- Panagiotelis, A., Athanasopoulos, G., Gamakumara, P. and Hyndman, R.J. (2021), Forecast reconciliation: A geometric view with new insights on bias correction, *International Journal of Forecasting*, 37, 1, 343–359. doi:[10.1016/j.ijforecast.2020.06.004](#)
- Stellato, B., Banjac, G., Goulart, P., Bemporad, A. and Boyd, S. (2020), OSQP: An Operator Splitting solver for Quadratic Programs, *Mathematical Programming Computation*, 12, 4, 637-672. doi:[10.1007/s12532020001792](#)
- Wickramasuriya, S.L., Athanasopoulos, G. and Hyndman, R.J. (2019), Optimal forecast reconciliation for hierarchical and grouped time series through trace minimization, *Journal of the American Statistical Association*, 114, 526, 804-819. doi:[10.1080/01621459.2018.1448825](#)
- Wickramasuriya, S. L., Turlach, B. A., and Hyndman, R. J. (2020). Optimal non-negative forecast reconciliation. *Statistics and Computing*, 30(5), 1167–1182. doi:[10.1007/s11222020099300](#)

Zhang, B., Kang, Y., Panagiotelis, A. and Li, F. (2023), Optimal reconciliation with immutable forecasts, *European Journal of Operational Research*, 308(2), 650–660. doi:[10.1016/j.ejor.2022.11.035](https://doi.org/10.1016/j.ejor.2022.11.035)

See Also

Regression-based reconciliation: [ctrec\(\)](#), [terec\(\)](#)

Cross-sectional framework: [csboot\(\)](#), [csbu\(\)](#), [cscov\(\)](#), [cslcc\(\)](#), [csmo\(\)](#), [csmvn\(\)](#), [cssmp\(\)](#), [cstd\(\)](#), [cstools\(\)](#)

Examples

```
set.seed(123)
# (2 x 3) base forecasts matrix (simulated), Z = X + Y
base <- matrix(rnorm(6, mean = c(20, 10, 10)), 2, byrow = TRUE)
# (10 x 3) in-sample residuals matrix (simulated)
res <- t(matrix(rnorm(n = 30), nrow = 3))

# Aggregation matrix for Z = X + Y
A <- t(c(1,1))
reco <- csrec(base = base, agg_mat = A, comb = "wls", res = res)

# Zero constraints matrix for Z - X - Y = 0
C <- t(c(1, -1, -1))
reco <- csrec(base = base, cons_mat = C, comb = "wls", res = res)

# Non negative reconciliation
# Making negative one of the base forecasts for variable Y
base[1,3] <- -base[1,3]
nnreco <- csrec(base = base, agg_mat = A, comb = "wls", res = res,
               nn = "osqp")
summary(nnreco)
```

cssmp

Cross-sectional Probabilistic Reconciliation (Sample Approach)

Description

This function performs cross-sectional probabilistic forecast reconciliation using a sample-based approach (Panagiotelis et al., 2023, Girolimetto et al., 2024) for linearly constrained (e.g., hierarchical or grouped) multiple time series. Given an array of L simulated base forecast draws, [cssmp\(\)](#) applies a chosen **FoReco** reconciliation independently to each draw, producing a coherent sample distribution of reconciled forecasts. Typical choices for the reconciliation include optimal combination ([csrec](#)) as well as top-down ([cstd](#)), middle-out ([csmo](#)), bottom-up ([csbu](#)), and level-conditional ([cslcc](#)) approaches.

Usage

```
cssmp(sample, fun = csrec, ...)
```

Arguments

sample	A $(h \times n \times L)$ numeric array containing the base forecasts samples to be reconciled; h is the forecast horizon, n is the total number of time series ($n = n_a + n_b$), and L is the sample size.
fun	A function performing the reconciliation, as implemented in FoReco .
...	Arguments passed on to fun

Value

A `distributional::dist_sample` of reconciled forecasts, of class `foreco` (see [foreco-class](#)).

References

- Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134–1151. doi:[10.1016/j.ijforecast.2023.10.003](#)
- Panagiotelis, A., Gamakumara, P., Athanasopoulos, G. and Hyndman, R.J. (2023), Probabilistic forecast reconciliation: Properties, evaluation and score optimisation, *European Journal of Operational Research* 306(2), 693–706. doi:[10.1016/j.ejor.2022.07.040](#)

See Also

Probabilistic reconciliation: [csmvn\(\)](#), [ctmvn\(\)](#), [ctsmv\(\)](#), [temvn\(\)](#), [tesmv\(\)](#)

Cross-sectional framework: [csboot\(\)](#), [csbu\(\)](#), [cscov\(\)](#), [cslcc\(\)](#), [csmo\(\)](#), [csmvn\(\)](#), [csrec\(\)](#), [cstd\(\)](#), [cstools\(\)](#)

Examples

```
set.seed(123)
A <- matrix(c(1,1,1,1, # Z = X + Y
              1,1,0,0, # X = XX + XY
              0,0,1,1), # Y = YX + YY
            nrow = 3, byrow = TRUE)
rownames(A) <- c("Z", "X", "Y")
colnames(A) <- c("XX", "XY", "YX", "YY")

# (100 x 7) base forecasts sample (simulated) for h = 1
base_h1 <- matrix(rnorm(100*7, mean = c(20, rep(10, 2), rep(5, 4))),
                  100, byrow = TRUE)

# (100 x 7) base forecasts sample (simulated) for h = 2
base_h2 <- matrix(rnorm(100*7, mean = c(20, rep(10, 2), rep(5, 4))),
                  100, byrow = TRUE)

# (2 x 7 x 100) base forecasts sample array with
# 2 forecast horizons, 7 time series and 100 sample
base_sample <- aperm(simplify2array(list(base_h1, base_h2)), c(3,2,1))

# Top-down probabilistic reconciliation
reco_dist_td <- cssmp(base_sample[, 1, , drop = FALSE], agg_mat = A,
                     fun = cstd, weights = c(0.3, 0.2, 0.1, 0.4))
```

```
# Middle-out probabilistic reconciliation
reco_dist_mo <- cssmp(base_sample[, c(2,3), , drop = FALSE], agg_mat = A,
                      fun = csmo, weights = c(0.3, 0.7, 0.8, 0.2),
                      id_rows = 2:3)

# Bottom-up probabilistic reconciliation
reco_dist_bu <- cssmp(base_sample[, -c(1:3), ], agg_mat = A, fun = csbu)

# Level conditional coherent probabilistic reconciliation
reco_dist_lcc <- cssmp(base_sample, agg_mat = A, fun = cslcc)

# Optimal cross-sectional probabilistic reconciliation
reco_dist_opt <- cssmp(base_sample, agg_mat = A)
```

cstd

*Cross-sectional Top-down Reconciliation***Description**

Top-down forecast reconciliation for genuine hierarchical/grouped time series (Gross and Sohl, 1990), where the forecast of a ‘Total’ (top-level series, expected to be positive) is disaggregated according to a proportional scheme (weights). Besides fulfilling any aggregation constraint, the top-down reconciled forecasts should respect two main properties:

- the top-level value remains unchanged;
- all the bottom time series reconciled forecasts are non-negative.

Usage

```
cstd(base, agg_mat, weights, normalize = TRUE)
```

Arguments

base	A $(h \times 1)$ numeric vector containing the top-level base forecast; h is the forecast horizon.
agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
weights	A $(h \times n_b)$ numeric matrix containing the proportions for the bottom time series; h is the forecast horizon, and n_b is the total number of bottom variables.
normalize	If TRUE (<i>default</i>), the weights will sum to 1.

Value

An object of class `foreco` (see [foreco-class](#)) with a $(h \times n)$ numeric matrix of cross-sectional reconciled forecasts.

References

Gross, C.W. and Sohl, J.E. (1990), Disaggregation methods to expedite product line forecasting. *Journal of Forecasting* 9(3), 233–254. doi:10.1002/for.3980090304

See Also

Top-down reconciliation: `cttd()`, `tetd()`

Cross-sectional framework: `csboot()`, `csbu()`, `cscov()`, `cslcc()`, `csmo()`, `csmvn()`, `csrec()`, `cssmp()`, `cstools()`

Examples

```
set.seed(123)
# Aggregation matrix for Z = X + Y, X = XX + XY and Y = YX + YY
A <- matrix(c(1,1,1,1,1,1,0,0,0,0,1,1), 3, byrow = TRUE)
# (3 x 1) top base forecasts vector (simulated), forecast horizon = 3
topf <- rnorm(3, 10)
# Same weights for different forecast horizons
fix_weights <- runif(4)
reco <- cstdd(base = topf, agg_mat = A, weights = fix_weights)

# Different weights for different forecast horizons
h_weights <- matrix(runif(4*3), 3, 4)
recoh <- cstdd(base = topf, agg_mat = A, weights = h_weights)
```

cstools

Cross-sectional Reconciliation Tools

Description

Some useful tools for the cross-sectional forecast reconciliation of a linearly constrained (e.g., hierarchical/grouped) multiple time series.

Usage

```
cstools(agg_mat, cons_mat, sparse = TRUE)
```

Arguments

<code>agg_mat</code>	A ($n_a \times n_b$) numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
<code>cons_mat</code>	A ($n_a \times n$) numeric matrix representing the cross-sectional zero constraints: each row represents a constraint equation, and each column represents a variable. The matrix can be of full rank, meaning the rows are linearly independent, but this is not a strict requirement, as the function allows for redundancy in the constraints.
<code>sparse</code>	Option to return sparse matrices (<i>default</i> is TRUE).

Value

A list with four elements:

<code>dim</code>	A vector containing information about the number of series for the complete system (n), for upper levels (na) and bottom level (nb).
<code>agg_mat</code>	The cross-sectional aggregation matrix.
<code>strc_mat</code>	The cross-sectional structural matrix.
<code>cons_mat</code>	The cross-sectional zero constraints matrix.

See Also

Cross-sectional framework: `csboot()`, `csbu()`, `cscov()`, `cslcc()`, `csmo()`, `csmvn()`, `csrec()`, `cssmp()`, `cstd()`

Utilities: `aggts()`, `as_ctmatrix()`, `as_tevector()`, `balance_hierarchy()`, `commat()`, `csprojmat()`, `ctprojmat()`, `cttools()`, `df2aggmat()`, `lcmat()`, `res2matrix()`, `set_bounds()`, `shrink_estim()`, `shrink_oasd()`, `teprojmat()`, `tetools()`, `unbalance_hierarchy()`

Examples

```
# Cross-sectional framework
# One level hierarchy A = [1 1]
A <- matrix(1, 1, 2)
obj <- cstools(agg_mat = A)
```

ctboot

Cross-temporal Joint Block Bootstrap

Description

Joint block bootstrap for generating probabilistic base forecasts that take into account the correlation between variables at different temporal aggregation orders (Girolimetto et al. 2023).

Usage

```
ctboot(model_list, boot_size, agg_order, block_size = 1, seed = NULL,
       xreg = NULL, ...)
```

Arguments

<code>model_list</code>	A list of p elements, one for each temporal level ordered from the lowest frequency (most temporally aggregated) to the highest frequency. Each element is a list with the n base forecasts models for each cross-sectional series. A <code>simulate()</code> function for each model has to be available and implemented according to the package. forecast , with the following mandatory parameters: <i>object</i> , <i>innov</i> , <i>future</i> , and <i>nsim</i> .
-------------------------	---

<code>boot_size</code>	The number of bootstrap replicates.
<code>agg_order</code>	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
<code>block_size</code>	Block size of the bootstrap, which is typically equivalent to the forecast horizon for the most temporally aggregated series.
<code>seed</code>	An integer seed.
<code>xreg</code>	An optional 3-d numeric array of dimensions $(n \times \text{boot_size}(k^* + m) \times N_{xreg})$ containing the new values of <code>xreg</code> to be used for forecasting ordered from the lowest frequency to the highest frequency (columns) for each variable (rows). It can contain NAs.
<code>...</code>	Additional arguments for the <code>simulate()</code> function.

Value

A list with `boot_size` matrix of size $(n \times (k^* + m)\text{block_size})$.

References

Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. doi:[10.1016/j.ijforecast.2023.10.003](https://doi.org/10.1016/j.ijforecast.2023.10.003)

See Also

Bootstrap samples: `csboot()`, `teboot()`

Cross-temporal framework: `ctbu()`, `ctcov()`, `ctlcc()`, `ctmo()`, `ctmvn()`, `ctrec()`, `ctsmp()`, `cttd()`, `cttools()`, `iterec()`, `tcsrec()`

Examples

```
set.seed(123)

# Minimal example functions: each "model" stores Gaussian residuals;
# simulate() draws new innovations (innov=NULL) or uses the supplied
# ones (innov given).
simple_model <- function(res) {
  structure(list(residuals = res, sigma = sd(res)), class = "simple_model")
}
simulate.simple_model <- function(object, nsim = 1, innov = NULL,
                                future = TRUE, ...) {
  if (is.null(innov)) {
    rnorm(nsim, mean = 0, sd = object$sigma)
  } else {
    as.numeric(innov)[seq_len(nsim)]
  }
}

# Cross-temporal hierarchy:
# - cross-sectional: Z = X + Y => n = 3
```

```

# - temporal: annual-quarterly => m = 4, kset = c(4, 2, 1), p = 3 levels
n <- 3
m <- 4
kset <- c(4, 2, 1)
n_obs_per_k <- 40 / kset

# Nested list: outer level = p temporal aggregation orders (low -> high
# frequency), inner level = n cross-sectional series.
model_list <- lapply(seq_along(kset), function(i) {
  lapply(seq_len(n), function(j) {
    simple_model(rnorm(n_obs_per_k[i]))
  })
})

# Joint block bootstrap: 50 replicates, block_size = 1
boot <- ctboot(model_list = model_list, boot_size = 50, agg_order = m,
               block_size = 1, seed = 1)

```

ctbu

Cross-temporal Bottom-up Reconciliation

Description

Cross-temporal bottom-up reconciled forecasts for all series at any temporal aggregation level are computed by appropriate summation of the high-frequency bottom base forecasts $\hat{\mathbf{B}}^{[1]}$:

$$\tilde{\mathbf{X}} = \mathbf{S}_{cs} \hat{\mathbf{B}}^{[1]} \mathbf{S}_{te}',$$

where $\mathbf{S}_{cs}$ and $\mathbf{S}_{te}$ are the cross-sectional and temporal structural matrices, respectively.

Usage

```
ctbu(base, agg_mat, agg_order, tew = "sum", sintz = FALSE, round = FALSE)
```

Arguments

base	A $(n_b \times hm)$ numeric matrix containing high-frequency bottom base forecasts; n_b is the total number of high-frequency bottom variables, m is the max aggregation order, and h is the forecast horizon for the lowest frequency time series.
agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).

sntz	Logical. If TRUE, the negative base forecasts are set to zero (Di Fonzo and Girolimetto, 2023; Girolimetto 2025) before applying bottom-up. <i>Default</i> is FALSE.
round	Logical. If TRUE, base forecasts are rounded before applying the bottom-up reconciliation. <i>Default</i> is FALSE.

Value

An object of class `foreco` (see [foreco-class](#)) with a $(n \times h(k^* + m))$ numeric matrix of cross-temporal reconciled forecasts.

References

Di Fonzo, T. and Girolimetto, D. (2023), Spatio-temporal reconciliation of solar forecasts, *Solar Energy*, 251, 13–29. [doi:10.1016/j.solener.2023.01.003](#)

See Also

Bottom-up reconciliation: [csbu\(\)](#), [tebu\(\)](#)

Cross-temporal framework: [ctboot\(\)](#), [ctcov\(\)](#), [ctlcc\(\)](#), [ctmo\(\)](#), [ctmvn\(\)](#), [ctrec\(\)](#), [ctsmp\(\)](#), [cttd\(\)](#), [cttools\(\)](#), [iterec\(\)](#), [tcsrec\(\)](#)

Examples

```
set.seed(123)
# Aggregation matrix for Z = X + Y
A <- t(c(1,1))
# (2 x 4) high frequency bottom base forecasts matrix (simulated),
# agg_order = 4 (annual-quarterly)
hfbts <- matrix(rnorm(4*2, 2.5), 2, 4)

reco <- ctbu(base = hfbts, agg_mat = A, agg_order = 4)

# Non negative reconciliation
hfbts[1,4] <- -hfbts[1,4] # Making negative one of the quarterly values for X
nnreco <- ctbu(base = hfbts, agg_mat = A, agg_order = 4, sntz = TRUE)
```

ctcov

Cross-temporal Covariance Matrix Approximation

Description

This function provides an approximation of the cross-temporal base forecasts errors covariance matrix using different reconciliation methods (Di Fonzo and Girolimetto, 2023, and Girolimetto et al., 2023).

Usage

```
ctcov(comb = "ols", agg_mat = NULL, agg_order = NULL, tew = "sum",
      res = NULL, n = NULL, mse = TRUE, shrink_fun = shrink_estim, ...)
```

Arguments

comb	A string specifying the reconciliation method. • For ordinary least squares reconciliation: – "ols" (<i>default</i>) - identity error covariance. • For weighted least squares reconciliation: – "str" - structural variances. – "csstr" - cross-sectional structural variances. – "testr" - temporal structural variances. – "wlsh" - hierarchy variances (uses res). – "wlsv" - series variances (uses res). • For generalized least squares (uses res) reconciliation: – "acov" - series auto-covariance. – "bdshr"/"bdsam" - shrunk/sample block diagonal cross-sectional covariance. – "Sshr"/"Ssam" - series shrunk/sample covariance. – "shr"/"sam" - shrunk/sample covariance. – "hbshr"/"hbsam" - shrunk/sample high frequency bottom time series covariance. – "bshr"/"bsam" - shrunk/sample bottom time series covariance. – "hshr"/"hsam" - shrunk/sample high frequency covariance. • Others (no for reconciliation): – "bu" - bottom-up covariance.
agg_mat	A ($n_a \times n_b$) numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
res	A ($n \times N(k^* + m)$) optional numeric matrix containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency (columns) for each variable (rows). This matrix is used to compute some covariance matrices.
n	Cross-sectional number of variables.
mse	If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected.
shrink_fun	Shrinkage function of the covariance matrix, shrink_estim (<i>default</i>).
...	Not used.

Value

A ($n(k^* + m) \times n(k^* + m)$) symmetric matrix.

References

Di Fonzo, T. and Girolimetto, D. (2023a), Cross-temporal forecast reconciliation: Optimal combination method and heuristic alternatives, *International Journal of Forecasting*, 39, 1, 39-57. [doi:10.1016/j.ijforecast.2021.08.004](https://doi.org/10.1016/j.ijforecast.2021.08.004)

Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. [doi:10.1016/j.ijforecast.2023.10.003](https://doi.org/10.1016/j.ijforecast.2023.10.003)

See Also

Cross-temporal framework: `ctboot()`, `ctbu()`, `ctlcc()`, `ctmo()`, `ctmvn()`, `ctrec()`, `ctsmp()`, `cttd()`, `cttools()`, `iterec()`, `tcsrec()`

Examples

```
set.seed(123)
# Aggregation matrix for Z = X + Y
A <- t(c(1,1))
# (3 x 70) in-sample residuals matrix (simulated),
# agg_order = 4 (annual-quarterly)
res <- rbind(rnorm(70), rnorm(70), rnorm(70))

cov1 <- ctcov("ols", n = 3, agg_order = 4)           # OLS
cov2 <- ctcov("str", agg_mat = A, agg_order = 4)     # STR
cov3 <- ctcov("csstr", agg_mat = A, agg_order = 4)   # CSSTR
cov4 <- ctcov("testr", n = 3, agg_order = 4)         # TESTR
cov5 <- ctcov("wlsv", agg_order = 4, res = res)      # WLSv
cov6 <- ctcov("wlsh", agg_order = 4, res = res)      # WLSh
cov7 <- ctcov("shr", agg_order = 4, res = res)       # SHR
cov8 <- ctcov("sam", agg_order = 4, res = res)       # SAM
cov9 <- ctcov("acov", agg_order = 4, res = res)      # ACOV
cov10 <- ctcov("Sshr", agg_order = 4, res = res)     # Sshr
cov11 <- ctcov("Ssam", agg_order = 4, res = res)     # Ssam
cov12 <- ctcov("hshr", agg_order = 4, res = res)     # Hshr
cov13 <- ctcov("hsam", agg_order = 4, res = res)     # Hsam
cov14 <- ctcov("hbshr", agg_mat = A, agg_order = 4, res = res) # HBshr
cov15 <- ctcov("hbsam", agg_mat = A, agg_order = 4, res = res) # HBsam
cov16 <- ctcov("bshr", agg_mat = A, agg_order = 4, res = res) # Bshr
cov17 <- ctcov("bsam", agg_mat = A, agg_order = 4, res = res) # Bsam
cov18 <- ctcov("bdshr", agg_order = 4, res = res)   # BDshr
cov19 <- ctcov("bdsam", agg_order = 4, res = res)   # Bdsam

# Custom covariance matrix
ctcov.ols2 <- function(comb, x) diag(x)
cov20 <- ctcov(comb = "ols2", x = 21) # == ctcov("ols", n = 3, agg_order = 4)
```

ctlcc	<i>Level Conditional Coherent Reconciliation for Cross-temporal Hierarchies</i>
-------	---

Description

This function implements a forecast reconciliation procedure inspired by the original proposal by Hollyman et al. (2021) for cross-temporal hierarchies. Level conditional coherent reconciled forecasts are conditional on (i.e., constrained by) the base forecasts of a specific upper level in the hierarchy (exogenous constraints). It also allows handling the linear constraints linking the variables endogenously (Di Fonzo and Girolimetto, 2022). The function can calculate Combined Conditional Coherent (CCC) forecasts as simple averages of Level-Conditional Coherent (LCC) and bottom-up reconciled forecasts, with either endogenous or exogenous constraints.

Usage

```
ctlcc(base, agg_mat, agg_order, tew = "sum", comb = "ols", res = NULL,
      approach = "proj", nn = NULL, settings = NULL, CCC = TRUE,
      const = "exogenous", hfbts = NULL, ...)
```

Arguments

base	A $(n \times h(k^* + m))$ numeric matrix containing the base forecasts to be reconciled; n is the total number of variables, m is the maximum aggregation order, and k^* is the sum of a chosen subset of the $p - 1$ factors of m (excluding m itself), and h is the forecast horizon for the lowest frequency time series. The row identifies a time series, and the forecasts in each row are ordered from the lowest frequency (most temporally aggregated) to the highest frequency.
agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
comb	A string specifying the reconciliation method. For a complete list, see ctcov .
res	A $(n \times N(k^* + m))$ optional numeric matrix containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency (columns) for each variable (rows). This matrix is used to compute some covariance matrices.
approach	A string specifying the approach used to compute the reconciled forecasts. Options include: "proj" (<i>default</i>): Projection approach according to Byron (1978, 1979). "strc": Structural approach as proposed by Hyndman et al. (2011).

	• "proj_osqp": Numerical solution using osqp for projection approach. • "strc_osqp": Numerical solution using osqp for structural approach.
nn	A string specifying the algorithm to compute non-negative forecasts: • "osqp": quadratic programming optimization (osqp solver, Girolimetto 2025). • "bpv": block principal pivoting algorithm (Wickramasuriya et al., 2020). • "nfca": negative forecasts correction algorithm (Kourentzes and Athanassopoulos, 2021; Girolimetto 2025). • "nnic": iterative non-negative reconciliation with immutable constraints (Girolimetto 2025). • "sntz": heuristic "set-negative-to-zero" (Di Fonzo and Girolimetto, 2023; Girolimetto 2025).
settings	A list of control parameters. • nn = "osqp" An object of class <code>osqpSettings</code> specifying settings for the osqp solver. For details, refer to the osqp documentation (Stellato et al., 2020) • nn = "bpv" – ptype = "fixed": permutation method: "random" or "fixed" – par = 10: the number of full exchange rules that may be attempted – tol = <code>sqrt(.Machine\$double.eps)</code>: the tolerance criteria – gtol = <code>sqrt(.Machine\$double.eps)</code>: the gradient tolerance criteria – itmax = 100: the maximum number of algorithm iterations • nn = "nfca" and nn = "nnic" – tol = <code>sqrt(.Machine\$double.eps)</code>: the tolerance criteria – itmax = 100: the maximum number of algorithm iterations • nn = "sntz" – type = "bu": the type of set-negative-to-zero heuristic: "bu" for bottom-up, "tdp" for top-down proportional, "tdsp" for top-down square proportional, "tdvw" for top-down variance weighted (the <code>res</code> param is used). See Girolimetto (2025) for details. – tol = <code>sqrt(.Machine\$double.eps)</code>: the tolerance identification of negative values
CCC	A logical value indicating whether the Combined Conditional Coherent reconciled forecasts reconciliation should include bottom-up forecasts (TRUE, <i>default</i>), or not.
const	A string specifying the reconciliation constraints: • "exogenous" (<i>default</i>): Fixes the top level of each sub-hierarchy. • "endogenous": Coherently revises both the top and bottom levels.
hfbts	A $(n \times mh)$ numeric matrix containing high frequency bottom base forecasts defined by the user. This parameter can be omitted if only base forecasts are used (see Di Fonzo and Girolimetto, 2024).
...	Arguments passed on to <code>ctcov</code> mse If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected. shrink_fun Shrinkage function of the covariance matrix, <code>shrink_estim</code> (<i>default</i>).

Value

An object of class `foreco` (see [foreco-class](#)) with a $(n \times h(k^* + m))$ numeric matrix of cross-temporal reconciled forecasts.

References

- Byron, R.P. (1978), The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 141, 3, 359-367. doi:[10.2307/2344807](#)
- Byron, R.P. (1979), Corrigenda: The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 142(3), 405. doi:[10.2307/2982515](#)
- Di Fonzo, T. and Girolimetto, D. (2024), Forecast combination-based forecast reconciliation: Insights and extensions, *International Journal of Forecasting*, 40(2), 490–514. doi:[10.1016/j.ijforecast.2022.07.001](#)
- Di Fonzo, T. and Girolimetto, D. (2023b) Spatio-temporal reconciliation of solar forecasts. *Solar Energy* 251, 13–29. doi:[10.1016/j.solener.2023.01.003](#)
- Girolimetto, D. (2025), Non-negative forecast reconciliation: Optimal methods and operational solutions. *Forecasting*, 7(4), 64; doi:[10.3390/forecast7040064](#)
- Hyndman, R.J., Ahmed, R.A., Athanasopoulos, G. and Shang, H.L. (2011), Optimal combination forecasts for hierarchical time series, *Computational Statistics & Data Analysis*, 55, 9, 2579-2589. doi:[10.1016/j.csda.2011.03.006](#)
- Kourentzes, N. and Athanasopoulos, G. (2021) Elucidate structure in intermittent demand series. *European Journal of Operational Research*, 288, 141-152. doi:[10.1016/j.ejor.2020.05.046](#)
- Hollyman, R., Petropoulos, F. and Tipping, M.E. (2021), Understanding forecast reconciliation. *European Journal of Operational Research*, 294, 149–160. doi:[10.1016/j.ejor.2021.01.017](#)
- Stellato, B., Banjac, G., Goulart, P., Bemporad, A. and Boyd, S. (2020), OSQP: An Operator Splitting solver for Quadratic Programs, *Mathematical Programming Computation*, 12, 4, 637-672. doi:[10.1007/s12532020001792](#)

See Also

Level conditional coherent reconciliation: [cslcc\(\)](#), [telcc\(\)](#)

Cross-temporal framework: [ctboot\(\)](#), [ctbu\(\)](#), [ctcov\(\)](#), [ctmo\(\)](#), [ctmvn\(\)](#), [ctrec\(\)](#), [ctsmpl\(\)](#), [cttd\(\)](#), [cttools\(\)](#), [iterec\(\)](#), [tcsrec\(\)](#)

Examples

```
set.seed(123)
# Aggregation matrix for Z = X + Y, X = XX + XY and Y = YX + YY
A <- matrix(c(1,1,1,1,1,1,0,0,0,0,1,1), 3, byrow = TRUE)
# (7 x 7) base forecasts matrix (simulated), agg_order = 4
base <- rbind(rnorm(7, rep(c(40, 20, 10), c(1, 2, 4))),
              rnorm(7, rep(c(20, 10, 5), c(1, 2, 4))),
              rnorm(7, rep(c(20, 10, 5), c(1, 2, 4))),
              rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))),
              rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))),
              rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))),
              rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))))
# (7 x 70) in-sample residuals matrix (simulated)
```

```

res <- matrix(rnorm(70*7), nrow = 7)
# (4 x 4) Naive high frequency bottom base forecasts vector:
# all forecasts are set equal to 2.5
naive <- matrix(2.5, 4, 4)

## EXOGENOUS CONSTRAINTS (Hollyman et al., 2021)
# Level Conditional Coherent (LCC) reconciled forecasts
exo_LC <- ctlcc(base = base, agg_mat = A, agg_order = 4, comb = "wlsh", nn = "osqp",
               hfbts = naive, res = res, CCC = FALSE)

# Combined Conditional Coherent (CCC) reconciled forecasts
exo_CCC <- ctlcc(base = base, agg_mat = A, agg_order = 4, comb = "wlsh",
               hfbts = naive, res = res, CCC = TRUE)

# Results detailed by level:
info_exo <- summary(exo_CCC)
# info_exo$lcc

## ENDOGENOUS CONSTRAINTS (Di Fonzo and Girolimetto, 2024)
# Level Conditional Coherent (LCC) reconciled forecasts
endo_LC <- ctlcc(base = base, agg_mat = A, agg_order = 4, comb = "wlsh",
               res = res, CCC = FALSE, const = "endogenous")

# Combined Conditional Coherent (CCC) reconciled forecasts
endo_CCC <- ctlcc(base = base, agg_mat = A, agg_order = 4, comb = "wlsh",
               res = res, CCC = TRUE, const = "endogenous")

# Results detailed by level:
info_endo <- summary(endo_CCC)
# info_endo$lcc

```

ctmo

Cross-temporal Middle-out Reconciliation

Description

The cross-temporal middle-out forecast reconciliation combines top-down ([cttd](#)) and bottom-up ([ctbu](#)) methods in the cross-temporal framework for genuine hierarchical/grouped time series. Given the base forecasts of an intermediate cross-sectional level l and aggregation order k , it performs

- a top-down approach for the aggregation orders $\geq k$ and cross-sectional levels $\geq l$;
- a bottom-up approach, otherwise.

Usage

```

ctmo(base, agg_mat, agg_order, weights, id_rows = 1, order = max(agg_order),
     tew = "sum", normalize = TRUE)

```

Arguments

base	A $(n_l \times hk)$ numeric matrix containing the l -level base forecasts of temporal aggregation order k ; n_l is the number of variables at level l , k is an aggregation order (a factor of m , and $1 < k < m$), m is the max aggregation order, and h is the forecast horizon for the lowest frequency time series.
agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
weights	A $(n_b \times hm)$ numeric matrix containing the proportions for each high-frequency bottom time series; n_b is the total number of high-frequency bottom variables, m is the max aggregation order, and h is the forecast horizon for the lowest frequency time series.
id_rows	A numeric vector indicating the l -level rows of <code>agg_mat</code> .
order	The intermediate fixed aggregation order k .
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
normalize	If TRUE (<i>default</i>), the weights will sum to 1.

Value

An object of class `foreco` (see [foreco-class](#)) with a $(n \times h(k^* + m))$ numeric matrix of cross-temporal reconciled forecasts.

See Also

Middle-out reconciliation: [csmo\(\)](#), [temo\(\)](#)

Cross-temporal framework: [ctboot\(\)](#), [ctbu\(\)](#), [ctcov\(\)](#), [ctlcc\(\)](#), [ctmvn\(\)](#), [ctrec\(\)](#), [ctsmp\(\)](#), [cttd\(\)](#), [cttools\(\)](#), [iterec\(\)](#), [tcsrec\(\)](#)

Examples

```
set.seed(123)
# Aggregation matrix for Z = X + Y, X = XX + XY and Y = YX + YY
A <- matrix(c(1,1,1,1,1,1,0,0,0,0,1,1), 3, byrow = TRUE)
# (2 x 6) base forecasts matrix (simulated), forecast horizon = 3
# and intermediate aggregation order k = 2 (max agg order = 4)
baseL2k2 <- rbind(rnorm(3*2, 5), rnorm(3*2, 5))

# Same weights for different forecast horizons, agg_order = 4
fix_weights <- matrix(runif(4*4), 4, 4)
reco <- ctmo(base = baseL2k2, id_rows = 2:3, agg_mat = A,
             order = 2, agg_order = 4, weights = fix_weights)

# Different weights for different forecast horizons
```

```
h_weights <- matrix(runif(4*4*3), 4, 3*4)
recoh <- ctmo(base = baseL2k2, id_rows = 2:3, agg_mat = A,
              order = 2, agg_order = 4, weights = h_weights)
```

ctmvn

Cross-temporal Gaussian Probabilistic Reconciliation

Description

This function performs cross-temporal probabilistic forecast reconciliation assuming a multivariate normal base forecast distribution (Girolimetto et al., 2024) for linearly constrained multiple time series observed across both cross-sectional and temporal dimensions (Di Fonzo and Girolimetto, 2023).

Usage

```
ctmvn(base, agg_mat, cons_mat, agg_order, tew = "sum", comb = "ols",
      res = NULL, approach = "proj", comb_base = comb,
      reduce_form = FALSE, ...)
```

Arguments

base	A $(n \times h(k^* + m))$ numeric matrix containing the base forecasts to be reconciled; n is the total number of variables, m is the maximum aggregation order, and k^* is the sum of a chosen subset of the $p - 1$ factors of m (excluding m itself), and h is the forecast horizon for the lowest frequency time series. The row identifies a time series, and the forecasts in each row are ordered from the lowest frequency (most temporally aggregated) to the highest frequency.
agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
cons_mat	A $(n_a \times n)$ numeric matrix representing the cross-sectional zero constraints: each row represents a constraint equation, and each column represents a variable. The matrix can be of full rank, meaning the rows are linearly independent, but this is not a strict requirement, as the function allows for redundancy in the constraints.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
comb	A string specifying the reconciliation method. For a complete list, see ctcov .
res	A $(n \times N(k^* + m))$ optional numeric matrix containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency (columns) for each variable (rows). This matrix is used to compute some covariance matrices.

approach	A string specifying the approach used to compute the reconciled forecasts. Options include: • "proj" (<i>default</i>): Projection approach according to Byron (1978, 1979). • "strc": Structural approach as proposed by Hyndman et al. (2011). • "proj_osqp": Numerical solution using osqp for projection approach. • "strc_osqp": Numerical solution using osqp for structural approach.
comb_base	A string specifying the base covariance matrix approach. For a complete list, see ctcov . Default is the equal to comb.
reduce_form	A logical parameter indicating whether the function should return the full distribution (FALSE, <i>default</i>) or only the distribution corresponding to the high-frequency bottom time series (TRUE).
...	Arguments passed on to ctcov
mse	If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected.
shrink_fun	Shrinkage function of the covariance matrix, shrink_estim (<i>default</i>).

Value

A [distributional::dist_multivariate_normal](#) of reconciled forecasts, of class `foreco` (see [foreco-class](#)).

References

- Byron, R.P. (1978), The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 141, 3, 359-367. doi:[10.2307/2344807](#)
- Byron, R.P. (1979), Corrigenda: The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 142(3), 405. doi:[10.2307/2982515](#)
- Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. doi:[10.1016/j.ijforecast.2023.10.003](#)
- Hyndman, R.J., Ahmed, R.A., Athanasopoulos, G. and Shang, H.L. (2011), Optimal combination forecasts for hierarchical time series, *Computational Statistics & Data Analysis*, 55, 9, 2579-2589. doi:[10.1016/j.csda.2011.03.006](#)
- Panagiotelis, A., Gamakumara, P., Athanasopoulos, G. and Hyndman, R.J. (2023), Probabilistic forecast reconciliation: Properties, evaluation and score optimisation, *European Journal of Operational Research* 306(2), 693–706. doi:[10.1016/j.ejor.2022.07.040](#)

See Also

Probabilistic reconciliation: [csmvn\(\)](#), [cssmp\(\)](#), [ctsmp\(\)](#), [temvn\(\)](#), [tesmp\(\)](#)

Cross-temporal framework: [ctboot\(\)](#), [ctbu\(\)](#), [ctcov\(\)](#), [ctlcc\(\)](#), [ctmo\(\)](#), [ctrec\(\)](#), [ctsmp\(\)](#), [cttd\(\)](#), [cttools\(\)](#), [iterec\(\)](#), [tcsrec\(\)](#)

Examples

```
set.seed(123)
# (3 x 7) base forecasts matrix (simulated), Z = X + Y and m = 4
base <- rbind(rnorm(7, rep(c(20, 10, 5), c(1, 2, 4))),
              rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))),
              rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))))
# (3 x 70) in-sample residuals matrix (simulated)
res <- rbind(rnorm(70), rnorm(70), rnorm(70))
A <- t(c(1,1))
reco_dist <- ctmvn(base = base, res = res, agg_mat = A, agg_order = 4)
```

ctprojmat	<i>Projection Matrix for Optimal Combination Cross-temporal Reconciliation</i>
-----------	--

Description

This function computes the projection or the mapping matrix $\mathbf{M}$ and $\mathbf{G}$, respectively, such that $\tilde{\mathbf{y}} = \mathbf{M}\hat{\mathbf{y}} = \mathbf{S}_{ct}\mathbf{G}\hat{\mathbf{y}}$, where $\tilde{\mathbf{y}}$ is the vector of the reconciled forecasts, $\hat{\mathbf{y}}$ is the vector of the base forecasts, $\mathbf{S}_{ct}$ is the cross-temporal structural matrix, and $\mathbf{M} = \mathbf{S}_{ct}\mathbf{G}$. For further information regarding on the structure of these matrices, refer to Girolimetto et al. (2023).

Usage

```
ctprojmat(agg_mat, cons_mat, agg_order, comb = "ols", res = NULL,
          mat = "M", tew = "sum", ...)
```

Arguments

agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
cons_mat	A $(n_a \times n)$ numeric matrix representing the cross-sectional zero constraints: each row represents a constraint equation, and each column represents a variable. The matrix can be of full rank, meaning the rows are linearly independent, but this is not a strict requirement, as the function allows for redundancy in the constraints.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
comb	A string specifying the reconciliation method. For a complete list, see ctcov .
res	A $(n \times N(k^* + m))$ optional numeric matrix containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency (columns) for each variable (rows). This matrix is used to compute some covariance matrices.
mat	A string specifying which matrix to return: "M" (<i>default</i>) for $\mathbf{M}$ and "G" for $\mathbf{G}$.

tew A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, *default*), "avg" (average), "first" (first value of the period), and "last" (last value of the period).

... Arguments passed on to [ctcov](#)

mse If TRUE (*default*) the errors used to compute the covariance matrix are not mean-corrected.

shrink_fun Shrinkage function of the covariance matrix, [shrink_estim](#) (*default*).

Value

The projection matrix **M** (mat = "M") or the mapping matrix **G** (mat = "G").

References

Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. doi:[10.1016/j.ijforecast.2023.10.003](https://doi.org/10.1016/j.ijforecast.2023.10.003)

See Also

Utilities: [aggts\(\)](#), [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [balance_hierarchy\(\)](#), [compmat\(\)](#), [csprojmat\(\)](#), [cstools\(\)](#), [cttools\(\)](#), [df2aggmat\(\)](#), [lcmat\(\)](#), [res2matrix\(\)](#), [set_bounds\(\)](#), [shrink_estim\(\)](#), [shrink_oasd\(\)](#), [teprojmat\(\)](#), [tetools\(\)](#), [unbalance_hierarchy\(\)](#)

Examples

```
# Cross-temporal framework (Z = X + Y, annual-quarterly)
A <- t(c(1,1)) # Aggregation matrix for Z = X + Y
Mct <- ctprojmat(agg_mat = A, agg_order = 4, comb = "ols")
Gct <- ctprojmat(agg_mat = A, agg_order = 4, comb = "ols", mat = "G")
```

ctrec

Optimal Combination Cross-temporal Reconciliation

Description

This function performs optimal (in least squares sense) combination cross-temporal forecast reconciliation (Di Fonzo and Girolimetto 2023a, Girolimetto et al. 2023). The reconciled forecasts are calculated using either a projection approach (Byron, 1978, 1979) or the equivalent structural approach by Hyndman et al. (2011). Non-negative (Di Fonzo and Girolimetto, 2023) and immutable reconciled forecasts can be considered.

Usage

```
ctrec(base, agg_mat, cons_mat, agg_order, tew = "sum", comb = "ols",
      res = NULL, approach = "proj", nn = NULL, settings = NULL,
      bounds = NULL, immutable = NULL, ...)
```

Arguments

base	A $(n \times h(k^* + m))$ numeric matrix containing the base forecasts to be reconciled; n is the total number of variables, m is the maximum aggregation order, and k^* is the sum of a chosen subset of the $p - 1$ factors of m (excluding m itself), and h is the forecast horizon for the lowest frequency time series. The row identifies a time series, and the forecasts in each row are ordered from the lowest frequency (most temporally aggregated) to the highest frequency.
agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
cons_mat	A $(n_a \times n)$ numeric matrix representing the cross-sectional zero constraints: each row represents a constraint equation, and each column represents a variable. The matrix can be of full rank, meaning the rows are linearly independent, but this is not a strict requirement, as the function allows for redundancy in the constraints.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
comb	A string specifying the reconciliation method. For a complete list, see ctcov .
res	A $(n \times N(k^* + m))$ optional numeric matrix containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency (columns) for each variable (rows). This matrix is used to compute some covariance matrices.
approach	A string specifying the approach used to compute the reconciled forecasts. Options include: "proj" (<i>default</i>): Projection approach according to Byron (1978, 1979). "strc": Structural approach as proposed by Hyndman et al. (2011). "proj_osqp": Numerical solution using osqp for projection approach. "strc_osqp": Numerical solution using osqp for structural approach.
nn	A string specifying the algorithm to compute non-negative forecasts: "osqp": quadratic programming optimization (osqp solver, Girolimetto 2025). "bpv": block principal pivoting algorithm (Wickramasuriya et al., 2020). "nfca": negative forecasts correction algorithm (Kourentzes and Athanassopoulos, 2021; Girolimetto 2025). "nnic": iterative non-negative reconciliation with immutable constraints (Girolimetto 2025). "sntz": heuristic "set-negative-to-zero" (Di Fonzo and Girolimetto, 2023; Girolimetto 2025).
settings	A list of control parameters. nn = "osqp" An object of class <code>osqpSettings</code> specifying settings for the osqp solver. For details, refer to the osqp documentation (Stellato et al., 2020)

	• <code>nn = "bpv"</code> – <code>ptype = "fixed"</code>: permutation method: "random" or "fixed" – <code>par = 10</code>: the number of full exchange rules that may be attempted – <code>tol = sqrt(.Machine\$double.eps)</code>: the tolerance criteria – <code>gtol = sqrt(.Machine\$double.eps)</code>: the gradient tolerance criteria – <code>itmax = 100</code>: the maximum number of algorithm iterations • <code>nn = "nfca"</code> and <code>nn = "nnic"</code> – <code>tol = sqrt(.Machine\$double.eps)</code>: the tolerance criteria – <code>itmax = 100</code>: the maximum number of algorithm iterations • <code>nn = "sntz"</code> – <code>type = "bu"</code>: the type of set-negative-to-zero heuristic: "bu" for bottom-up, "tdp" for top-down proportional, "tdsp" for top-down square proportional, "tdvw" for top-down variance weighted (the <code>res</code> param is used). See Girolimetto (2025) for details. – <code>tol = sqrt(.Machine\$double.eps)</code>: the tolerance identification of negative values
bounds	A matrix (see set_bounds) with 5 columns ($i, k, j, lower, upper$), such that • Column 1 represents the cross-sectional series ($i = 1, \dots, n$). • Column 2 represents the temporal aggregation order ($k = m, \dots, 1$). • Column 3 represents the temporal forecast horizon ($j = 1, \dots, m/k$). • Columns 4 and 5 indicates the <i>lower</i> and <i>upper</i> bounds, respectively.
immutable	A matrix with three columns (i, k, j), such that • Column 1 represents the cross-sectional series ($i = 1, \dots, n$). • Column 2 represents the temporal aggregation order ($k = m, \dots, 1$). • Column 3 represents the temporal forecast horizon ($j = 1, \dots, m/k$). For example, when working with a quarterly multivariate time series ($n = 3$): • <code>t(c(1, 4, 1))</code> - Fix the one step ahead annual forecast of the first time series. • <code>t(c(2, 1, 2))</code> - Fix the two step ahead quarterly forecast of the second time series.
...	Arguments passed on to ctcov <code>mse</code> If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected. <code>shrink_fun</code> Shrinkage function of the covariance matrix, shrink_estim (<i>default</i>).

Value

An object of class `foreco` (see [foreco-class](#)) with a $(n \times h(k^* + m))$ numeric matrix of cross-temporal reconciled forecasts.

References

- Byron, R.P. (1978), The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 141, 3, 359-367. doi:[10.2307/2344807](https://doi.org/10.2307/2344807)
- Byron, R.P. (1979), Corrigenda: The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 142(3), 405. doi:[10.2307/2982515](https://doi.org/10.2307/2982515)
- Di Fonzo, T. and Girolimetto, D. (2023a), Cross-temporal forecast reconciliation: Optimal combination method and heuristic alternatives, *International Journal of Forecasting*, 39, 1, 39-57. doi:[10.1016/j.ijforecast.2021.08.004](https://doi.org/10.1016/j.ijforecast.2021.08.004)
- Di Fonzo, T. and Girolimetto, D. (2023), Spatio-temporal reconciliation of solar forecasts, *Solar Energy*, 251, 13–29. doi:[10.1016/j.solener.2023.01.003](https://doi.org/10.1016/j.solener.2023.01.003)
- Girolimetto, D. (2025), Non-negative forecast reconciliation: Optimal methods and operational solutions. *Forecasting*, 7(4), 64; doi:[10.3390/forecast7040064](https://doi.org/10.3390/forecast7040064)
- Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. doi:[10.1016/j.ijforecast.2023.10.003](https://doi.org/10.1016/j.ijforecast.2023.10.003)
- Hyndman, R.J., Ahmed, R.A., Athanasopoulos, G. and Shang, H.L. (2011), Optimal combination forecasts for hierarchical time series, *Computational Statistics & Data Analysis*, 55, 9, 2579-2589. doi:[10.1016/j.csda.2011.03.006](https://doi.org/10.1016/j.csda.2011.03.006)
- Kourentzes, N. and Athanasopoulos, G. (2021) Elucidate structure in intermittent demand series. *European Journal of Operational Research*, 288, 141-152. doi:[10.1016/j.ejor.2020.05.046](https://doi.org/10.1016/j.ejor.2020.05.046)
- Stellato, B., Banjac, G., Goulart, P., Bemporad, A. and Boyd, S. (2020), OSQP: An Operator Splitting solver for Quadratic Programs, *Mathematical Programming Computation*, 12, 4, 637-672. doi:[10.1007/s12532020001792](https://doi.org/10.1007/s12532020001792)
- Wickramasuriya, S. L., Turlach, B. A., and Hyndman, R. J. (2020). Optimal non-negative forecast reconciliation. *Statistics and Computing*, 30(5), 1167–1182. doi:[10.1007/s11222020099300](https://doi.org/10.1007/s11222020099300)

See Also

Regression-based reconciliation: `csrec()`, `terec()`

Cross-temporal framework: `ctboot()`, `ctbu()`, `ctcov()`, `ctlcc()`, `ctmo()`, `ctmvn()`, `ctsmp()`, `cttd()`, `cttools()`, `iterec()`, `tcsrec()`

Examples

```
set.seed(123)
# (3 x 7) base forecasts matrix (simulated), Z = X + Y and m = 4
base <- rbind(rnorm(7, rep(c(20, 10, 5), c(1, 2, 4))),
              rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))),
              rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))))
# (3 x 70) in-sample residuals matrix (simulated)
res <- rbind(rnorm(70), rnorm(70), rnorm(70))

A <- t(c(1,1)) # Aggregation matrix for Z = X + Y
m <- 4 # from quarterly to annual temporal aggregation
reco <- ctrec(base = base, agg_mat = A, agg_order = m,
              comb = "wlsv", res = res)
```

```

C <- t(c(1, -1, -1)) # Zero constraints matrix for  $Z - X - Y = 0$ 
reco <- ctrec(base = base, cons_mat = C, agg_order = m,
              comb = "wlsv", res = res)

# Immutable reconciled forecasts
# Fix all the quarterly forecasts of the second variable.
imm_mat <- expand.grid(i = 2, k = 1, j = 1:4)
immreco <- ctrec(base = base, cons_mat = C, agg_order = m, comb = "wlsv",
                 res = res, immutable = imm_mat)

# Non negative reconciliation
# Making negative one of the quarterly base forecasts for variable X
base[2,7] <- -2*base[2,7]
nnreco <- ctrec(base = base, cons_mat = C, agg_order = m, comb = "wlsv",
                 res = res, nn = "osqp")
summary(nnreco)

```

ctsmp

Cross-temporal Probabilistic Reconciliation (Sample Approach)

Description

This function performs cross-temporal probabilistic forecast reconciliation using a sample-based approach (Girolimetto et al., 2024) for linearly constrained multiple time series observed across both cross-sectional and temporal dimensions (Di Fonzo and Girolimetto, 2023). Given a $(n \times h(k^* + m) \times L)$ array of simulated base forecast draws, `ctsmp()` applies a chosen **FoReco** cross-temporal reconciliation independently to each draw, enforcing coherence simultaneously over aggregation levels and across series. Typical choices for the reconciliation include optimal combination (`ctrec`) as well as top-down (`cttd`), middle-out (`ctmo`), bottom-up (`ctbu`), and level-conditional (`ctlcc`) approaches.

Usage

```
ctsmp(sample, agg_order, fun = ctrec, ...)
```

Arguments

sample	A $(n \times h(k^* + m) \times L)$ numeric array containing the base forecasts samples to be reconciled; n is the total number of variables, m is the max. order of temporal aggregation, k^* is the sum of (a subset of) $(p - 1)$ factors of m , excluding m , h is the forecast horizon for the lowest frequency time series, and L is the sample size. The row identifies a time series, and the forecasts in each row are ordered from the lowest frequency (most temporally aggregated) to the highest frequency.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .

fun A function performing the reconciliation, as implemented in **FoReco**.
 ... Arguments passed on to fun

Value

A `distributional::dist_sample` of reconciled forecasts, of class `foreco` (see `foreco-class`).

References

Di Fonzo, T. and Girolimetto, D. (2023a), Cross-temporal forecast reconciliation: Optimal combination method and heuristic alternatives, *International Journal of Forecasting*, 39, 1, 39-57. doi:[10.1016/j.ijforecast.2021.08.004](https://doi.org/10.1016/j.ijforecast.2021.08.004)

Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. doi:[10.1016/j.ijforecast.2023.10.003](https://doi.org/10.1016/j.ijforecast.2023.10.003)

See Also

Probabilistic reconciliation: `csmvn()`, `cssmp()`, `ctmvn()`, `temvn()`, `tesmp()`
 Cross-temporal framework: `ctboot()`, `ctbu()`, `ctcov()`, `ctlcc()`, `ctmo()`, `ctmvn()`, `ctrec()`, `cttd()`, `cttools()`, `iterec()`, `tcsrec()`

Examples

```
set.seed(123)
A <- t(c(1,1)) # Aggregation matrix for Z = X + Y
m <- 4 # from quarterly to annual temporal aggregation

# (100 x 14) base forecasts sample matrix (simulated), m = 4, h = 2, n = 3
sample <- simplify2array(lapply(1:100, function(x){
  rbind(rnorm(14, rep(c(20, 10, 5), 2*c(1, 2, 4))),
        rnorm(14, rep(c(10, 5, 2.5), 2*c(1, 2, 4))),
        rnorm(14, rep(c(10, 5, 2.5), 2*c(1, 2, 4))))
}))
# (3 x 70) in-sample residuals matrix (simulated)
res <- rbind(rnorm(70), rnorm(70), rnorm(70))

# Top-down probabilistic reconciliation
reco_dist_td <- ctsmp(sample[1, 1:2, ], drop = FALSE, agg_order = m,
                      agg_mat = A, fun = cttd, weights = matrix(runif(8), 2))

# Middle-out probabilistic reconciliation
reco_dist_mo <- ctsmp(sample[1, 3:6, ], drop = FALSE, agg_order = m,
                      agg_mat = A, fun = ctmo, weights = matrix(runif(8), 2),
                      id_rows = 1, order = 2)

# Bottom-up probabilistic reconciliation
reco_dist_bu <- ctsmp(sample[-1,-c(1:6)], , agg_order = m, agg_mat = A,
                      fun = ctbu)

# Level conditional coherent probabilistic reconciliation
reco_dist_lcc <- ctsmp(sample, agg_order = m, agg_mat = A, fun = ctlcc)
```

```
# Optimal cross-sectional probabilistic reconciliation
reco_dist_opt <- ctsmp(sample, agg_order = m, agg_mat = A, res = res,
                      comb = "bdshr")
```

cttd

Cross-temporal Top-down Reconciliation

Description

Top-down forecast reconciliation for cross-temporal hierarchical/grouped time series, where the forecast of a ‘Total’ (top-level series, expected to be positive) is disaggregated according to a proportional scheme (weights). Besides fulfilling any aggregation constraint, the top-down reconciled forecasts should respect two main properties:

- the top-level value remains unchanged;
- all the bottom time series reconciled forecasts are non-negative.

Usage

```
cttd(base, agg_mat, agg_order, weights, tew = "sum", normalize = TRUE)
```

Arguments

base	A $(hm \times 1)$ numeric vector containing top- and m temporal aggregated level base forecasts; m is the max aggregation order, and h is the forecast horizon for the lowest frequency time series.
agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
weights	A $(n_b \times hm)$ numeric matrix containing the proportions for each high-frequency bottom time series; n_b is the total number of high-frequency bottom variables, m is the max aggregation order, and h is the forecast horizon for the lowest frequency time series.
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
normalize	If TRUE (<i>default</i>), the weights will sum to 1.

Value

An object of class `foreco` (see [foreco-class](#)) with a $(n \times h(k^* + m))$ numeric matrix of cross-temporal reconciled forecasts.

See Also

Top-down reconciliation: `cstd()`, `tetd()`

Cross-temporal framework: `ctboot()`, `ctbu()`, `ctcov()`, `ctlcc()`, `ctmo()`, `ctmvn()`, `ctrec()`, `ctsmpl()`, `cttools()`, `iterec()`, `tcsrec()`

Examples

```
set.seed(123)
# (3 x 1) top base forecasts vector (simulated), forecast horizon = 3
topf <- rnorm(3, 10)
A <- t(c(1,1)) # Aggregation matrix for Z = X + Y

# Same weights for different forecast horizons, agg_order = 4
fix_weights <- matrix(runif(4*2), 2, 4)
reco <- cttd(base = topf, agg_mat = A, agg_order = 4, weights = fix_weights)

# Different weights for different forecast horizons
h_weights <- matrix(runif(4*2*3), 2, 3*4)
recoh <- cttd(base = topf, agg_mat = A, agg_order = 4, weights = h_weights)
```

cttools

Cross-temporal Reconciliation Tools

Description

Some useful tools for the cross-temporal forecast reconciliation of a linearly constrained (e.g., hierarchical/grouped) multiple time series.

Usage

```
cttools(agg_mat, cons_mat, agg_order, tew = "sum", fh = 1, sparse = TRUE)
```

Arguments

agg_mat	A ($n_a \times n_b$) numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
cons_mat	A ($n_a \times n$) numeric matrix representing the cross-sectional zero constraints: each row represents a constraint equation, and each column represents a variable. The matrix can be of full rank, meaning the rows are linearly independent, but this is not a strict requirement, as the function allows for redundancy in the constraints.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .

tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
fh	Forecast horizon for the lowest frequency (most temporally aggregated) time series (<i>default</i> is 1).
sparse	Option to return sparse matrices (<i>default</i> is TRUE).

Value

A list with four elements:

dim	A vector containing information about the number of series for the complete system (n), for upper levels (na) and bottom level (nb), the maximum aggregation order (m), the number of factor (p), the partial (ks) and total sum (kt) of factors.
set	The vector of the temporal aggregation orders (in decreasing order).
agg_mat	The cross-temporal aggregation matrix.
strc_mat	The cross-temporal structural matrix.
cons_mat	The cross-temporal zero constraints matrix.

See Also

Cross-temporal framework: [ctboot\(\)](#), [ctbu\(\)](#), [ctcov\(\)](#), [ctlcc\(\)](#), [ctmo\(\)](#), [ctmvn\(\)](#), [ctrec\(\)](#), [ctsmp\(\)](#), [cttd\(\)](#), [iterec\(\)](#), [tcsrec\(\)](#)

Utilities: [aggts\(\)](#), [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [balance_hierarchy\(\)](#), [compmat\(\)](#), [csprojmat\(\)](#), [cstools\(\)](#), [ctprojmat\(\)](#), [df2aggmat\(\)](#), [lcmat\(\)](#), [res2matrix\(\)](#), [set_bounds\(\)](#), [shrink_estim\(\)](#), [shrink_oasd\(\)](#), [teprojmat\(\)](#), [tetools\(\)](#), [unbalance_hierarchy\(\)](#)

Examples

```
# Cross-temporal framework
A <- t(c(1,1)) # Aggregation matrix for Z = X + Y
m <- 4 # from quarterly to annual temporal aggregation
cttools(agg_mat = A, agg_order = m)
```

df2aggmat

Cross-sectional Aggregation Matrix of a Dataframe

Description

This function allows the user to easily build the $(n_a \times n_b)$ cross-sectional aggregation matrix starting from a data frame.

Usage

```
df2aggmat(formula, data, sep = "_", sparse = TRUE, top_label = "Total",
           verbose = TRUE)
```

Arguments

formula	Specification of the hierarchical structure: grouped hierarchies are specified using $\sim g1 * g2$ and nested hierarchies are specified using $\sim \text{parent} / \text{child}$. Mixtures of the two formulations are also possible, like $\sim g1 * (\text{grandparent} / \text{parent} / \text{child})$.
data	A dataset in which each column contains the values of the variables in the formula and each row identifies a bottom level time series.
sep	Character to separate the names of the aggregated series, (<i>default</i> is "_").
sparse	Option to return sparse matrices (<i>default</i> is TRUE).
top_label	Label of the top level variable (<i>default</i> is "Total").
verbose	If TRUE (<i>default</i>), hierarchy informations are printed.

Value

A (na x nb) matrix.

See Also

Utilities: [aggts\(\)](#), [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [balance_hierarchy\(\)](#), [compmat\(\)](#), [csprojmat\(\)](#), [cstools\(\)](#), [ctprojmat\(\)](#), [cttools\(\)](#), [lcmat\(\)](#), [res2matrix\(\)](#), [set_bounds\(\)](#), [shrink_estim\(\)](#), [shrink_oasd\(\)](#), [teprojmat\(\)](#), [tertools\(\)](#), [unbalance_hierarchy\(\)](#)

Examples

```
## Balanced hierarchy
#
#           T
#   |-----|
#   A         B
# |---|   |--|--|
# AA  AB  BA BB BC
# Names of the bottom level variables
data_bts <- data.frame(X1 = c("A", "A", "B", "B", "B"),
                      X2 = c("A", "B", "A", "B", "C"),
                      stringsAsFactors = FALSE)
# Cross-sectional aggregation matrix
agg_mat <- df2aggmat(~ X1 / X2, data_bts, sep = "", verbose = FALSE)

## Unbalanced hierarchy
#
#           T
#   |-----|-----|
#   A         B         C
# |---|   |--|--|   |--|
# AA  AB  BA  BB  CA  CB
# |----|           |----|
```

```

# AAA AAB      BBA BBB
# Names of the bottom level variables
data_bts <- data.frame(X1 = c("A", "A", "A", "B", "B", "B", "C", "C"),
                      X2 = c("A", "A", "B", "A", "B", "B", "A", "B"),
                      X3 = c("A", "B", NA, NA, "A", "B", NA, NA),
                      stringsAsFactors = FALSE)

# Cross-sectional aggregation matrix
agg_mat <- df2aggmat(~ X1 / X2 / X3, data_bts, sep = "", verbose = FALSE)

## Group of two hierarchies
#   T      T      T | A | B | C
# |--|--| X |--| -> -+-----+-----+
# A B C   M F     M | AM | BM | CM
#                   F | AF | BF | CF
# Names of the bottom level variables
data_bts <- data.frame(X1 = c("A", "A", "B", "B", "C", "C"),
                      Y1 = c("M", "F", "M", "F", "M", "F"),
                      stringsAsFactors = FALSE)

# Cross-sectional aggregation matrix
agg_mat <- df2aggmat(~ Y1 * X1, data_bts, sep = "", verbose = FALSE)

```

foreco-class

FoReco Reconciliation Class

Description

The `foreco` class represents reconciled forecasts produced by the `FoReco` package. It extends a numeric matrix, vector, or distributional object with additional attributes that store metadata about the reconciliation procedure (framework, function used, forecast type, and other reconciliation-specific information). The class provides dedicated methods for printing, summarising, extracting components and visualising reconciled forecasts.

Usage

```

new_foreco_class(reco, framework, rfun, rtype, rinfo = NULL, nninfo = NULL)

## S3 method for class 'foreco'
summary(object, keep_forecasts = TRUE, ...)

## S3 method for class 'summary_foreco'
print(x, n_row = 4L, n_col = 6L, ...)

## S3 method for class 'foreco'
print(x, n_row = NULL, n_col = NULL, ...)

## S3 method for class 'foreco'
plot(x, cs = NULL, te = 1, alpha = 0.95, ...)

```

```
## S3 method for class 'foreco'
components(
  object,
  cs = NULL,
  te = NULL,
  keep_names = FALSE,
  temporal_names = NULL,
  simplify = FALSE,
  ...
)

drop_foreco_class(x)
```

Arguments

<code>reco</code>	A numeric matrix/vector (when <code>rtype = "point"</code>) or a distributional object (when <code>rtype = "probabilistic"</code>).
<code>framework</code>	A character string identifying the reconciliation framework. Must be one of "cross-sectional", "temporal", or "cross-temporal".
<code>rfun</code>	A character scalar with the name of the FoReco function that produced the reconciled forecasts (e.g. "csrec", "terec", "ctrec").
<code>rtype</code>	A character string indicating the type of reconciled forecasts. Must be one of "point" or "probabilistic".
<code>rinfo</code>	An optional named list with additional reconciliation information (e.g. covariance approximation <code>comb</code> , machine-learning approach <code>ml</code> , non-negativity flag <code>nn</code> , cross-sectional size <code>cs_n</code> , temporal aggregation set <code>te_set</code> , forecast horizon <code>forecast_horizon</code> , level-conditional reconciled forecasts <code>lcc</code>).
<code>nninfo</code>	An optional matrix with information about the non-negativity procedure applied during reconciliation. Stored as the <code>info</code> field of the "FoReco" attribute.
<code>keep_forecasts</code>	Logical; if TRUE (the default), the reconciled forecasts are stored in the <code>rf</code> element of the returned <code>summary_foreco</code> object (and therefore printed at the end of the summary). Set to FALSE to obtain a lighter summary object that omits them.
<code>...</code>	Additional arguments passed to the underlying methods (e.g. <code>print()</code>).
<code>x, object</code>	An object of class <code>foreco</code> .
<code>n_row, n_col</code>	Integers giving the maximum number of rows and columns to display when printing. If NULL (the default) all rows/columns are shown. When the matrix is truncated, a summary line reports how many rows and columns have been omitted.
<code>cs</code>	Optional integer vector selecting the cross-sectional series to keep. If NULL (the default) all series are returned.
<code>te</code>	Optional vector (numeric or character) selecting the temporal aggregation orders to keep, matched against the elements of <code>te_set</code> . If NULL (the default) all orders are returned.
<code>alpha</code>	Nominal coverage of the prediction interval drawn by <code>plot.foreco()</code> for probabilistic forecasts. Defaults to 0.95.

<code>keep_names</code>	Logical. If TRUE, the row/column names of the reconciled forecasts are preserved in the output of <code>components.foreco()</code> . Defaults to FALSE.
<code>temporal_names</code>	Optional character vector of labels for the temporal aggregation orders returned by <code>components.foreco()</code> . Its length must match the number of returned orders, otherwise a warning is emitted and the default "k-..." labels are used.
<code>simplify</code>	Logical. If TRUE and the result consists of a single component, the underlying object (a matrix or vector) is returned directly instead of being wrapped in a named list of length one. If FALSE (default), the output is always a named list.

Details

`new_foreco_class()` is the low-level constructor. It is exported so that companion packages can produce objects that integrate with FoReco's `print()`, `summary()`, `plot()` and `components()` methods.

`plot.foreco()` draws the reconciled forecasts as line/point plots. For probabilistic forecasts (`rtype = "probabilistic"`) it also overlays a shaded central $\alpha * 100\%$ prediction interval, built from the $(1 - \alpha)/2$ and $1 - (1 - \alpha)/2$ quantiles of the distributional object; the median is shown as a dashed line and the interval limits as dotted lines.

Value

A `foreco` object extending the reconciled forecasts/distributions with reconciliation metadata.

`components.foreco()` returns a named list of reconciled forecasts split by temporal aggregation order. For the cross-sectional framework the list has a single element "k-1".

Examples

```
set.seed(123)
# Aggregation matrix for Z = X + Y
A <- t(c(1, 1))
bts <- matrix(rnorm(6, mean = 10), 3, 2)
reco <- csbu(base = bts, agg_mat = A)

# Print and summarise the reconciled forecasts
print(reco)
print(reco, n_row = 2, n_col = 2)
summary(reco)
summary(reco, keep_forecasts = FALSE)

# Extract reconciled forecasts by temporal aggregation order
components(reco)

# Remove the foreco class
drop_foreco_class(reco)
```

itagdp

*Italian Quarterly National Accounts Dataset***Description**

A subset of the data used by Girolimetto et al. (2023) from the Italian Quarterly National Accounts (output, income and expenditure sides) spanning the period 2000:Q1-2019:Q4.

Usage

```
# 21 time series of the Italian Quarterly National Accounts
itagdp

# 'agg_mat' and 'cons_mat' for the output side
outside

# 'agg_mat' and 'cons_mat' for the expenditure side
expside

# 'agg_mat' and 'cons_mat' for the income side
incside

# zero constraints matrix encompassing output, expenditure and income sides
gdpconsmat
```

Format

itagdp is a (80×21) ts object, corresponding to 21 time series of the Italian Quarterly National Accounts (2000:Q1-2019:Q4).

outside, income and expenditure are lists with two elements:

- agg_mat contains the (1×2) , (2×4) , or (6×8) aggregation matrix according to output, income or expenditure side, respectively.
- cons_mat contains the (1×3) , (2×6) , or (6×14) zero constraints matrix according to output, income or expenditure side, respectively.

gdpconsmat is the complete (9×21) zero constraints matrix encompassing output, expenditure and income sides.

Source

<https://ec.europa.eu/eurostat/web/national-accounts/>

References

Girolimetto, D. and Di Fonzo, T. (2023), Point and probabilistic forecast reconciliation for general linearly constrained multiple time series, *Statistical Methods & Applications*, 33, 581-607. doi:10.1007/s10260023007386.

iterec

*Iterative Cross-temporal Reconciliation***Description**

This function performs the iterative procedure described in Di Fonzo and Girolimetto (2023), which produces cross-temporally reconciled forecasts by alternating forecast reconciliation along one single dimension (either cross-sectional or temporal) at each iteration step.

Usage

```
iterec(base, cslist, telist, res = NULL, itmax = 100, tol = 1e-5,
       type = "tcs", norm = "inf", verbose = TRUE)
```

Arguments

base	A $(n \times h(k^* + m))$ numeric matrix containing the base forecasts to be reconciled; n is the total number of variables, m is the maximum aggregation order, and k^* is the sum of a chosen subset of the $p - 1$ factors of m (excluding m itself), and h is the forecast horizon for the lowest frequency time series. The row identifies a time series, and the forecasts in each row are ordered from the lowest frequency (most temporally aggregated) to the highest frequency.
cslist	A list of elements for the cross-sectional reconciliation. See csrec for a complete list (excluded base and res).
telist	A list of elements for the temporal reconciliation. See terec for a complete list (excluded base and res).
res	A $(n \times N(k^* + m))$ optional numeric matrix containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency (columns) for each variable (rows). This matrix is used to compute some covariance matrices.
itmax	Max number of iteration (100, <i>default</i>).
tol	Convergence tolerance (1e-5, <i>default</i>).
type	A string specifying the uni-dimensional reconciliation order: temporal and then cross-sectional ("tcs") or cross-sectional and then temporal ("cst").
norm	Norm used to calculate the temporal and the cross-sectional incoherence: infinity norm ("inf", <i>default</i>), one norm ("one"), and 2-norm ("two").
verbose	If TRUE, reconciliation information are printed.

Value

An object of class `foreco` (see [foreco-class](#)) with a $(n \times h(k^* + m))$ numeric matrix of cross-temporal reconciled forecasts.

References

Di Fonzo, T. and Girolimetto, D. (2023), Cross-temporal forecast reconciliation: Optimal combination method and heuristic alternatives, *International Journal of Forecasting*, 39, 1, 39-57. [doi:10.1016/j.ijforecast.2021.08.004](https://doi.org/10.1016/j.ijforecast.2021.08.004)

See Also

Cross-temporal framework: `ctboot()`, `ctbu()`, `ctcov()`, `ctlcc()`, `ctmo()`, `ctmvn()`, `ctrec()`, `ctsmp()`, `cttd()`, `cttools()`, `tcsrec()`

Examples

```
set.seed(123)
# (3 x 7) base forecasts matrix (simulated), Z = X + Y and m = 4
base <- rbind(rnorm(7, rep(c(20, 10, 5), c(1, 2, 4))),
              rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))),
              rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))))
# (3 x 70) in-sample residuals matrix (simulated)
res <- rbind(rnorm(70), rnorm(70), rnorm(70))

A <- t(c(1,1)) # Aggregation matrix for Z = X + Y
m <- 4 # from quarterly to annual temporal aggregation

rite <- iterec(base = base,
               cslist = list(agg_mat = A, comb = "shr"),
               telist = list(agg_order = m, comb = "wlsv"),
               res = res)
```

lcmat

Linear Combination (Aggregation) Matrix for a General Linearly Constrained Multiple Time Series

Description

This function transforms a general (possibly redundant) zero constraints matrix into a linear combination (aggregation) matrix $\mathbf{A}_{cs}$. When working with a general linearly constrained multiple (n -variate) time series, getting a linear combination matrix $\mathbf{A}_{cs}$ is a critical step to obtain a structural-like representation such that

$$\mathbf{C}_{cs} = [\mathbf{I} \quad -\mathbf{A}],$$

where $\mathbf{C}_{cs}$ is the full rank zero constraints matrix (Girolimetto and Di Fonzo, 2023).

Usage

```
lcmat(cons_mat, method = "rref", tol = sqrt(.Machine$double.eps),
      verbose = FALSE, sparse = TRUE)
```

Arguments

cons_mat	A ($r \times n$) numeric matrix representing the cross-sectional zero constraints.
method	Method to use: "rref" for the Reduced Row Echelon Form through Gauss-Jordan elimination (<i>default</i>), or "qr" for the (pivoting) QR decomposition (Strang, 2019).
tol	Tolerance for the "rref" or "qr" method.
verbose	If TRUE, intermediate steps are printed (<i>default</i> is FALSE).
sparse	Option to return a sparse matrix (<i>default</i> is TRUE).

Value

A list with two elements: (i) the linear combination (aggregation) matrix (agg_mat) and (ii) the vector of the column permutations (pivot).

References

Girolimetto, D. and Di Fonzo, T. (2023), Point and probabilistic forecast reconciliation for general linearly constrained multiple time series, *Statistical Methods & Applications*, 33, 581-607. [doi:10.1007/s10260023007386](https://doi.org/10.1007/s10260023007386).

Strang, G. (2019), *Linear algebra and learning from data*, Wellesley, Cambridge Press.

See Also

Utilities: [aggts\(\)](#), [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [balance_hierarchy\(\)](#), [commat\(\)](#), [csprojmat\(\)](#), [cstools\(\)](#), [ctprojmat\(\)](#), [cttools\(\)](#), [df2aggmat\(\)](#), [res2matrix\(\)](#), [set_bounds\(\)](#), [shrink_estim\(\)](#), [shrink_oasd\(\)](#), [teprojmat\(\)](#), [tertools\(\)](#), [unbalance_hierarchy\(\)](#)

Examples

```
# Two hierarchy sharing the same top-level variable,
# but not sharing the bottom variables
#           X           X
#   |-----|   |-----|
#   A         B   C         D
#   |---|
# A1   A2
# 1) X = C + D,
# 2) X = A + B,
# 3) A = A1 + A2.
cons_mat <- matrix(c(1,-1,-1,0,0,0,0,
                    1,0,0,-1,-1,0,0,
                    0,0,0,1,0,-1,-1), nrow = 3, byrow = TRUE)
obj <- lcmat(cons_mat = cons_mat, verbose = TRUE)
agg_mat <- obj$agg_mat # linear combination matrix
pivot <- obj$pivot # Pivot vector
```

set_bounds

Set Bounds for Bounded Forecast Reconciliation

Description

This function defines the bounds matrix considering cross-sectional, temporal, or cross-temporal frameworks. The output matrix can be used as input for the bounds parameter in functions such as [csrec](#), [terec](#), or [ctrec](#), to perform bounded reconciliations.

Usage

```
set_bounds(n, k, h, lb = -Inf, ub = Inf, approach = "osqp", bounds = NULL)
```

Arguments

n	A $(b \times 1)$ vector representing the i th cross-sectional series ($i = 1, \dots, n$), where b is the number of bounds to be set.
k	A $(b \times 1)$ vector specifying the temporal aggregation orders ($k = m, \dots, 1$).
h	A $(b \times 1)$ vector representing the forecast horizons ($j = 1, \dots, m/k$).
lb, ub	A $(b \times 1)$ vector of lower and upper bounds.
approach	A string specifying the algorithm to compute bounded reconciled forecasts: "osqp": quadratic programming optimization (osqp solver). "sftb": heuristic "set-forecasts-to-bounds", which adjusts the reconciled forecasts to be within specified bounds without further optimization.
bounds	A matrix of previous bounds to be added. If not specified, new bounds will be computed.

Value

A numeric matrix representing the computed bounds, which can be:

- Cross-sectional $(b \times 3)$ matrix for cross-sectional reconciliation ([csrec](#)).
- Temporal $(b \times 4)$ matrix for temporal reconciliation ([terec](#)).
- Cross-temporal $(b \times 5)$ matrix for cross-temporal reconciliation ([ctrec](#)).

See Also

Utilities: [aggts\(\)](#), [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [balance_hierarchy\(\)](#), [commat\(\)](#), [csprojmat\(\)](#), [cstools\(\)](#), [ctprojmat\(\)](#), [cttools\(\)](#), [df2aggmat\(\)](#), [lcmat\(\)](#), [res2matrix\(\)](#), [shrink_estim\(\)](#), [shrink_oasd\(\)](#), [teprojmat\(\)](#), [tetools\(\)](#), [unbalance_hierarchy\(\)](#)

Examples

```
# Example 1
# Two cross-sectional series (i = 2,3),
# with each series required to be between 0 and 1.
n <- c(2, 3)
lb <- c(0, 0)
ub <- c(1,1)
bounds_mat <- set_bounds(n = c(2, 3),
                        lb = rep(0, 2), # or lb = 0
                        ub = rep(1, 2)) # or ub = 1

# Example 2
# All the monthly values are between 0 and 1.
bounds_mat <- set_bounds(k = rep(1, 12), # or k = 1
                        h = 1:12,
                        lb = rep(0, 12), # or lb = 0
                        ub = rep(1, 12)) # or ub = 1

# Example 3
# For two cross-sectional series (i = 2,3),
# all the monthly values are between 0 and 1.
bounds_mat <- set_bounds(n = rep(c(2, 3), each = 12),
                        k = 1,
                        h = rep(1:12, 2),
                        lb = 0, # or lb = 0
                        ub = 1) # or ub = 1
```

shrink_estim

*Shrinkage of the Covariance Matrix***Description**

Shrinkage of the covariance matrix according to Schäfer and Strimmer (2005).

Usage

```
shrink_estim(x, mse = TRUE)
```

Arguments

<code>x</code>	A numeric matrix containing the in-sample residuals or validation errors.
<code>mse</code>	If TRUE (<i>default</i>), the residuals used to compute the covariance matrix are not mean-corrected.

Value

A shrunk covariance matrix.

References

Schäfer, J.L. and Strimmer, K. (2005), A shrinkage approach to large-scale covariance matrix estimation and implications for functional genomics, *Statistical Applications in Genetics and Molecular Biology*, 4, 1. doi:10.2202/15446115.1175

See Also

Utilities: `aggts()`, `as_ctmatrix()`, `as_tevector()`, `balance_hierarchy()`, `commat()`, `csprojmat()`, `cstools()`, `ctprojmat()`, `cttools()`, `df2aggmat()`, `lcmat()`, `res2matrix()`, `set_bounds()`, `shrink_oasd()`, `teprojmat()`, `tetools()`, `unbalance_hierarchy()`

Examples

```
set.seed(123)
# Simulated in-sample residuals: 50 observations of a 4-variate process
res <- matrix(rnorm(50 * 4), nrow = 50, ncol = 4)
# Schafer-Strimmer shrunk covariance matrix
shr <- shrink_estim(res)
# Shrinkage intensity selected by the procedure
attr(shr, "lambda")
```

shrink_oasd

Shrinkage of the Covariance Matrix Using the Oracle Approximation

Description

Shrinkage of the covariance matrix according to the Oracle Approximating Shrinkage (OAS) of Chen et al. (2009) and Ando and Xiao (2023).

Usage

```
shrink_oasd(x, mse = TRUE)
```

Arguments

<code>x</code>	A numeric matrix containing the in-sample residuals or validation errors.
<code>mse</code>	If TRUE (<i>default</i>), the residuals used to compute the covariance matrix are not mean-corrected.

Value

A shrunk covariance matrix.

References

Ando, S., and Xiao, M. (2023), High-dimensional covariance matrix estimation: shrinkage toward a diagonal target. *IMF Working Papers*, 2023(257), A001.

Chen, Y., Wiesel, A., and Hero, A. O. (2009), Shrinkage estimation of high dimensional covariance matrices, *2009 IEEE international conference on acoustics, speech and signal processing*, 2937–2940. IEEE.

See Also

Utilities: [aggts\(\)](#), [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [balance_hierarchy\(\)](#), [commat\(\)](#), [csprojmat\(\)](#), [cstools\(\)](#), [ctprojmat\(\)](#), [cttools\(\)](#), [df2aggmat\(\)](#), [lcmat\(\)](#), [res2matrix\(\)](#), [set_bounds\(\)](#), [shrink_estim\(\)](#), [teprojmat\(\)](#), [tertools\(\)](#), [unbalance_hierarchy\(\)](#)

Examples

```
set.seed(123)
# Simulated in-sample residuals: 50 observations of a 4-variate process
res <- matrix(rnorm(50 * 4), nrow = 50, ncol = 4)
# Oracle Approximating Shrinkage (OAS) covariance matrix
shr <- shrink_oasd(res)
# Shrinkage intensity selected by the procedure
attr(shr, "lambda")
```

tcsrec

Heuristic Cross-temporal Reconciliation

Description

[tcsrec](#) replicates the procedure by Kourentzes and Athanasopoulos (2019): (i) for each time series the forecasts at any temporal aggregation order are reconciled using temporal hierarchies; (ii) time-by-time cross-sectional reconciliation is performed; and (iii) the projection matrices obtained at step (ii) are then averaged and used to cross-sectionally reconcile the forecasts obtained at step (i). In [cstrec](#), the order of application of the two reconciliation steps (temporal first, then cross-sectional), is inverted compared to [tcsrec](#) (Di Fonzo and Girolimetto, 2023).

Usage

```
# First-temporal-then-cross-sectional forecast reconciliation
tcsrec(base, cslist, telist, res = NULL, avg = "KA")

# First-cross-sectional-then-temporal forecast reconciliation
cstrec(base, cslist, telist, res = NULL)
```

Arguments

base	A $(n \times h(k^* + m))$ numeric matrix containing the base forecasts to be reconciled; n is the total number of variables, m is the maximum aggregation order, and k^* is the sum of a chosen subset of the $p - 1$ factors of m (excluding m itself), and h is the forecast horizon for the lowest frequency time series. The row identifies a time series, and the forecasts in each row are ordered from the lowest frequency (most temporally aggregated) to the highest frequency.
cslist	A list of elements for the cross-sectional reconciliation. See csrec for a complete list (excluded base and res).
telist	A list of elements for the temporal reconciliation. See terec for a complete list (excluded base and res).
res	A $(n \times N(k^* + m))$ optional numeric matrix containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency (columns) for each variable (rows). This matrix is used to compute some covariance matrices.
avg	If <code>avg = "KA"</code> (<i>default</i>), the final projection matrix M is the one proposed by Kourentzes and Athanasopoulos (2019), otherwise it is calculated as simple average of all the involved projection matrices at step 2 of the procedure (see Di Fonzo and Girolimetto, 2023).

Value

An object of class `foreco` (see [foreco-class](#)) with a $(n \times h(k^* + m))$ numeric matrix of cross-temporal reconciled forecasts.

Warning

The two-step heuristic reconciliation allows considering non negativity constraints only in the first step. This means that non-negativity is not guaranteed in the final reconciled values.

References

- Di Fonzo, T. and Girolimetto, D. (2023), Cross-temporal forecast reconciliation: Optimal combination method and heuristic alternatives, *International Journal of Forecasting*, 39, 1, 39-57. [doi:10.1016/j.ijforecast.2021.08.004](#)
- Kourentzes, N. and Athanasopoulos, G. (2019), Cross-temporal coherent forecasts for Australian tourism, *Annals of Tourism Research*, 75, 393-409. [doi:10.1016/j.annals.2019.02.001](#)

See Also

Cross-temporal framework: [ctboot\(\)](#), [ctbu\(\)](#), [ctcov\(\)](#), [ctlcc\(\)](#), [ctmo\(\)](#), [ctmvn\(\)](#), [ctrec\(\)](#), [ctsmpl\(\)](#), [cttd\(\)](#), [cttools\(\)](#), [iterec\(\)](#)

Examples

```
set.seed(123)
# (3 x 7) base forecasts matrix (simulated), Z = X + Y and m = 4
base <- rbind(rnorm(7, rep(c(20, 10, 5), c(1, 2, 4))),
```

```

      rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))),
      rnorm(7, rep(c(10, 5, 2.5), c(1, 2, 4))))
# (3 x 70) in-sample residuals matrix (simulated)
res <- rbind(rnorm(70), rnorm(70), rnorm(70))

A <- t(c(1,1)) # Aggregation matrix for Z = X + Y
m <- 4 # from quarterly to annual temporal aggregation

rtcs <- tcsrec(base = base,
  cslist = list(agg_mat = A, comb = "shr"),
  telist = list(agg_order = m, comb = "wlsv"),
  res = res)

rcst <- cstrec(base = base,
  cslist = list(agg_mat = A, comb = "shr"),
  telist = list(agg_order = m, comb = "wlsv"),
  res = res)

```

teboot

Temporal Joint Block Bootstrap

Description

Joint block bootstrap for generating probabilistic base forecasts that take into account the correlation between different temporal aggregation orders (Girolimetto et al. 2023).

Usage

```
teboot(model_list, boot_size, agg_order, block_size = 1, seed = NULL,
  xreg = NULL, ...)
```

Arguments

<code>model_list</code>	A list of all the p base forecasts models ordered from the lowest frequency (most temporally aggregated) to the highest frequency. A <code>simulate()</code> function for each model has to be available and implemented according to the package forecast , with the following mandatory parameters: <i>object</i> , <i>innov</i> , <i>future</i> , and <i>nsim</i> .
<code>boot_size</code>	The number of bootstrap replicates.
<code>agg_order</code>	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
<code>block_size</code>	Block size of the bootstrap, which is typically equivalent to the forecast horizon for the most temporally aggregated series.
<code>seed</code>	An integer seed.
<code>xreg</code>	A $(\text{block_size}(k^* + m) \times N_{xreg})$ optional numeric matrix containing the new values of <code>xreg</code> to be used for forecasting ordered from the lowest frequency to the highest frequency. It can contains NAs.
<code>...</code>	Additional arguments for the <code>simulate()</code> function.

Value

A $(\text{boot_size} \times (k^* + m)\text{block_size})$ matrix.

References

Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. doi:[10.1016/j.ijforecast.2023.10.003](https://doi.org/10.1016/j.ijforecast.2023.10.003)

See Also

Bootstrap samples: [csboot\(\)](#), [ctboot\(\)](#)

Temporal framework: [tebu\(\)](#), [tecov\(\)](#), [telcc\(\)](#), [temo\(\)](#), [temvn\(\)](#), [terec\(\)](#), [tesmp\(\)](#), [tetd\(\)](#), [tertools\(\)](#)

Examples

```
set.seed(123)

# Minimal example functions: each "model" stores Gaussian residuals;
# simulate() draws new innovations (innov=NULL) or uses the supplied
# ones (innov given).
simple_model <- function(res) {
  structure(list(residuals = res, sigma = sd(res)), class = "simple_model")
}
simulate.simple_model <- function(object, nsim = 1, innov = NULL,
                                  future = TRUE, ...) {
  if (is.null(innov)) {
    rnorm(nsim, mean = 0, sd = object$sigma)
  } else {
    as.numeric(innov)[seq_len(nsim)]
  }
}

# Temporal hierarchy: annual-quarterly, m = 4
# Aggregation orders k = 4, 2, 1 => k* + m = 1 + 2 + 4 = 7 models,
# ordered from the lowest frequency (annual) to the highest (quarterly).
m <- 4
kset <- c(4, 2, 1)          # k = 4 (annual), 2 (semi), 1 (quarterly)
n_obs_per_k <- 40 / kset    # residuals available at each frequency

model_list <- lapply(seq_along(kset), function(i) {
  simple_model(rnorm(n_obs_per_k[i]))
}))

# Joint block bootstrap: 100 replicates, block_size = 1 (one annual step)
boot <- teboot(model_list = model_list, boot_size = 100, agg_order = m,
               block_size = 1, seed = 1)
```

tebu

*Temporal Bottom-up Reconciliation***Description**

Temporal bottom-up reconciled forecasts at any temporal aggregation level are computed by appropriate aggregation of the high-frequency base forecasts, $\hat{\mathbf{x}}^{[1]}$:

$$\tilde{\mathbf{x}} = \mathbf{S}_{te} \hat{\mathbf{x}}^{[1]},$$

where $\mathbf{S}_{te}$ is the temporal structural matrix.

Usage

```
tebu(base, agg_order, tew = "sum", sntz = FALSE, round = FALSE)
```

Arguments

base	A $(hm \times 1)$ numeric vector containing the high-frequency base forecasts; m is the max. temporal aggregation order, and h is the forecast horizon for the lowest frequency time series.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
sntz	Logical. If TRUE, the negative base forecasts are set to zero (Di Fonzo and Girolimetto, 2023; Girolimetto 2025) before applying bottom-up. <i>Default</i> is FALSE.
round	Logical. If TRUE, base forecasts are rounded before applying the bottom-up reconciliation. <i>Default</i> is FALSE.

Value

An object of class `foreco` (see [foreco-class](#)) with a $(h(k^* + m) \times 1)$ numeric vector of temporal reconciled forecasts.

References

Di Fonzo, T. and Girolimetto, D. (2023), Spatio-temporal reconciliation of solar forecasts, *Solar Energy*, 251, 13–29. doi:[10.1016/j.solener.2023.01.003](https://doi.org/10.1016/j.solener.2023.01.003)

See Also

Bottom-up reconciliation: [csbu\(\)](#), [ctbu\(\)](#)

Temporal framework: [teboot\(\)](#), [tecov\(\)](#), [telcc\(\)](#), [temo\(\)](#), [temvn\(\)](#), [terec\(\)](#), [tesmp\(\)](#), [tetd\(\)](#), [tertools\(\)](#)

Examples

```
set.seed(123)
# (4 x 1) high frequency base forecasts vector (simulated),
# agg_order = 4 (annual-quarterly)
hfts <- rnorm(4, 5)

reco <- tebu(base = hfts, agg_order = 4)

# Non negative reconciliation
hfts[4] <- -hfts[4] # Making negative one of the quarterly base forecasts
nnreco <- tebu(base = hfts, agg_order = 4, sintz = TRUE)
```

tecov

Temporal Covariance Matrix Approximation

Description

This function provides an approximation of the temporal base forecasts errors covariance matrix using different reconciliation methods (see Di Fonzo and Girolimetto, 2023).

Usage

```
tecov(comb, agg_order = NULL, tew = "sum", res = NULL, mse = TRUE,
      shrink_fun = shrink_estim, ...)
```

Arguments

- | | |
|-----------|--|
| comb | <p>A string specifying the covariance approximation method.</p> <ul style="list-style-type: none"> • For ordinary least squares reconciliation: <ul style="list-style-type: none"> – "ols" (<i>default</i>) - identity error covariance. • For weighted least squares reconciliation: <ul style="list-style-type: none"> – "str" - structural variances. – "wlsh" - hierarchy variances (uses res). – "wlsv" - series variances (uses res). • For generalized least squares (uses res) reconciliation: <ul style="list-style-type: none"> – "acov" - series auto-covariance. – "strar1" - structural Markov covariance. – "sar1" - series Markov covariance. – "har1" - hierarchy Markov covariance. – "shr"/"sam" - shrunk/sample covariance. • Others (no for reconciliation): <ul style="list-style-type: none"> – "bu" - bottom-up covariance. |
| agg_order | <p>Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m.</p> |

tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
res	A $(N(k^* + m) \times 1)$ optional numeric vector containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency. This vector is used to compute come covariance matrices.
mse	If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected.
shrink_fun	Shrinkage function of the covariance matrix, shrink_estim (<i>default</i>)
...	Not used.

Value

A $((k^* + m) \times (k^* + m))$ symmetric matrix.

References

Di Fonzo, T. and Girolimetto, D. (2023a), Cross-temporal forecast reconciliation: Optimal combination method and heuristic alternatives, *International Journal of Forecasting*, 39, 1, 39-57. [doi:10.1016/j.ijforecast.2021.08.004](https://doi.org/10.1016/j.ijforecast.2021.08.004)

See Also

Temporal framework: [teboot\(\)](#), [tebu\(\)](#), [telcc\(\)](#), [temo\(\)](#), [temvn\(\)](#), [terec\(\)](#), [tesmp\(\)](#), [tetd\(\)](#), [tertools\(\)](#)

Examples

```
# (7 x 70) in-sample residuals matrix (simulated), agg_order = 4
res <- rnorm(70)

cov1 <- tecov("ols", agg_order = 4)           # OLS
cov2 <- tecov("str", agg_order = 4)           # STRC
cov3 <- tecov("wlsv", agg_order = 4, res = res) # WLSv
cov4 <- tecov("wlsh", agg_order = 4, res = res) # WLSH
cov5 <- tecov("acov", agg_order = 4, res = res) # ACOV
cov6 <- tecov("strar1", agg_order = 4, res = res) # STRAR1
cov7 <- tecov("har1", agg_order = 4, res = res) # HAR1
cov8 <- tecov("sar1", agg_order = 4, res = res) # SAR1
cov9 <- tecov("shr", agg_order = 4, res = res) # SHR
cov10 <- tecov("sam", agg_order = 4, res = res) # SAM

# Custom covariance matrix
tecov.ols2 <- function(comb, x) diag(x)
tecov(comb = "ols2", x = 7) # == tecov("ols", agg_order = 4)
```

Description

This function implements a forecast reconciliation procedure inspired by the original proposal by Hollyman et al. (2021) for temporal hierarchies. Level conditional coherent reconciled forecasts are conditional on (i.e., constrained by) the base forecasts of a specific upper level in the hierarchy (exogenous constraints). It also allows handling the linear constraints linking the variables endogenously (Di Fonzo and Girolimetto, 2022). The function can calculate Combined Conditional Coherent (CCC) forecasts as simple averages of Level-Conditional Coherent (LCC) and bottom-up reconciled forecasts, with either endogenous or exogenous constraints.

Usage

```
telcc(base, agg_order, tew = "sum", comb = "ols", res = NULL,
      approach = "proj", nn = NULL, settings = NULL, CCC = TRUE,
      const = "exogenous", hfts = NULL, ...)
```

Arguments

base	A $(h(k^* + m) \times 1)$ numeric vector containing the base forecasts to be reconciled, ordered from lowest to highest frequency; m is the maximum aggregation order, k^* is the sum of a chosen subset of the $p - 1$ factors of m (excluding m itself) and h is the forecast horizon for the lowest frequency time series.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
comb	A string specifying the reconciliation method. For a complete list, see tecov .
res	A $(N(k^* + m) \times 1)$ optional numeric vector containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency. This vector is used to compute come covariance matrices.
approach	A string specifying the approach used to compute the reconciled forecasts. Options include: "proj" (<i>default</i>): Projection approach according to Byron (1978, 1979). "strc": Structural approach as proposed by Hyndman et al. (2011). "proj_osqp": Numerical solution using osqp for projection approach. "strc_osqp": Numerical solution using osqp for structural approach.
nn	A string specifying the algorithm to compute non-negative forecasts: "osqp": quadratic programming optimization (osqp solver, Girolimetto 2025). "bpv": block principal pivoting algorithm (Wickramasuriya et al., 2020).

	• "nfca": negative forecasts correction algorithm (Kourentzes and Athanassopoulos, 2021; Girolimetto 2025). • "nnic": iterative non-negative reconciliation with immutable constraints (Girolimetto 2025). • "sntz": heuristic "set-negative-to-zero" (Di Fonzo and Girolimetto, 2023; Girolimetto 2025).
settings	A list of control parameters. • nn = "osqp" An object of class <code>osqpSettings</code> specifying settings for the osqp solver. For details, refer to the osqp documentation (Stellato et al., 2020) • nn = "bpv" – ptype = "fixed": permutation method: "random" or "fixed" – par = 10: the number of full exchange rules that may be attempted – tol = <code>sqrt(.Machine\$double.eps)</code>: the tolerance criteria – gtol = <code>sqrt(.Machine\$double.eps)</code>: the gradient tolerance criteria – itmax = 100: the maximum number of algorithm iterations • nn = "nfca" and nn = "nnic" – tol = <code>sqrt(.Machine\$double.eps)</code>: the tolerance criteria – itmax = 100: the maximum number of algorithm iterations • nn = "sntz" – type = "bu": the type of set-negative-to-zero heuristic: "bu" for bottom-up, "tdp" for top-down proportional, "tdsp" for top-down square proportional, "tdvw" for top-down variance weighted (the <code>res</code> param is used). See Girolimetto (2025) for details. – tol = <code>sqrt(.Machine\$double.eps)</code>: the tolerance identification of negative values
CCC	A logical value indicating whether the Combined Conditional Coherent reconciled forecasts reconciliation should include bottom-up forecasts (TRUE, <i>default</i>), or not.
const	A string specifying the reconciliation constraints: • "exogenous" (<i>default</i>): Fixes the top level of each sub-hierarchy. • "endogenous": Coherently revises both the top and bottom levels.
hfts	A $(mh \times 1)$ numeric vector containing high frequency base forecasts defined by the user. This parameter can be omitted if only base forecasts in base are used (see Di Fonzo and Girolimetto, 2024).
...	Arguments passed on to tecov
	mse If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected. shrink_fun Shrinkage function of the covariance matrix, shrink_estim (<i>default</i>)

Value

An object of class `foreco` (see [foreco-class](#)) with a $(h(k^* + m) \times 1)$ numeric vector of temporal reconciled forecasts.

References

- Byron, R.P. (1978), The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 141, 3, 359-367. doi:10.2307/2344807
- Byron, R.P. (1979), Corrigenda: The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 142(3), 405. doi:10.2307/2982515
- Di Fonzo, T. and Girolimetto, D. (2024), Forecast combination-based forecast reconciliation: Insights and extensions, *International Journal of Forecasting*, 40(2), 490–514. doi:10.1016/j.ijforecast.2022.07.001
- Di Fonzo, T. and Girolimetto, D. (2023b) Spatio-temporal reconciliation of solar forecasts. *Solar Energy* 251, 13–29. doi:10.1016/j.solener.2023.01.003
- Girolimetto, D. (2025), Non-negative forecast reconciliation: Optimal methods and operational solutions. *Forecasting*, 7(4), 64; doi:10.3390/forecast7040064
- Hyndman, R.J., Ahmed, R.A., Athanasopoulos, G. and Shang, H.L. (2011), Optimal combination forecasts for hierarchical time series, *Computational Statistics & Data Analysis*, 55, 9, 2579-2589. doi:10.1016/j.csda.2011.03.006
- Kourentzes, N. and Athanasopoulos, G. (2021) Elucidate structure in intermittent demand series. *European Journal of Operational Research*, 288, 141-152. doi:10.1016/j.ejor.2020.05.046
- Hollyman, R., Petropoulos, F. and Tipping, M.E. (2021), Understanding forecast reconciliation. *European Journal of Operational Research*, 294, 149–160. doi:10.1016/j.ejor.2021.01.017
- Stellato, B., Banjac, G., Goulart, P., Bemporad, A. and Boyd, S. (2020), OSQP: An Operator Splitting solver for Quadratic Programs, *Mathematical Programming Computation*, 12, 4, 637-672. doi:10.1007/s12532020001792

See Also

Level conditional coherent reconciliation: `cslcc()`, `ctlcc()`

Temporal framework: `teboot()`, `tebu()`, `tecov()`, `temo()`, `temvn()`, `terec()`, `tesmp()`, `tetd()`, `tetools()`

Examples

```
set.seed(123)
# (7 x 1) base forecasts vector (simulated), agg_order = 4
base <- rnorm(7, rep(c(20, 10, 5), c(1, 2, 4)))
# (70 x 1) in-sample residuals vector (simulated)
res <- rnorm(70)
# (4 x 1) Naive high frequency base forecasts vector: all forecasts are set equal to 2.5
naive <- rep(2.5, 4)

## EXOGENOUS CONSTRAINTS
# Level Conditional Coherent (LCC) reconciled forecasts
exo_LC <- telcc(base = base, agg_order = 4, comb = "wlsh", hfts = naive,
               res = res, CCC = FALSE)

# Combined Conditional Coherent (CCC) reconciled forecasts
exo_CCC <- telcc(base = base, agg_order = 4, comb = "wlsh", hfts = naive,
               res = res, CCC = TRUE)
```

```

# Results detailed by level:
info_exo <- summary(exo_CCC)
# info_exo$lcc

## ENDOGENOUS CONSTRAINTS
# Level Conditional Coherent (LCC) reconciled forecasts
endo_LC <- telcc(base = base, agg_order = 4, comb = "wlsh", res = res,
                 CCC = FALSE, const = "endogenous")

# Combined Conditional Coherent (CCC) reconciled forecasts
endo_CCC <- telcc(base = base, agg_order = 4, comb = "wlsh", res = res,
                  CCC = TRUE, const = "endogenous")

# Results detailed by level:
info_endo <- summary(endo_CCC)
# info_endo$lcc

```

temo

Temporal Middle-out Reconciliation

Description

The middle-out forecast reconciliation for temporal hierarchies combines top-down ([tetd](#)) and bottom-up ([tebu](#)) methods. Given the base forecasts of an intermediate temporal aggregation order k , it performs

- a top-down approach for the aggregation orders $< k$;
- a bottom-up approach for the aggregation orders $> k$.

Usage

```
temo(base, agg_order, weights, order = max(agg_order), tew = "sum",
     normalize = TRUE)
```

Arguments

base	A $(hk \times 1)$ numeric vector containing the temporal aggregated base forecasts of order k ; k is an aggregation order (a factor of m , and $1 < k < m$), m is the max aggregation order, and h is the forecast horizon for the lowest frequency time series.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
weights	A $(hm \times 1)$ numeric vector containing the proportions for the high-frequency time series; m is the max aggregation order, and h is the forecast horizon for the lowest frequency time series.
order	The intermediate fixed aggregation order k .

tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
normalize	If TRUE (<i>default</i>), the weights will sum to 1.

Value

An object of class `foreco` (see [foreco-class](#)) with a $(h(k^* + m) \times 1)$ numeric vector of temporal reconciled forecasts.

See Also

Middle-out reconciliation: [csmo\(\)](#), [ctmo\(\)](#)

Temporal framework: [teboot\(\)](#), [tebu\(\)](#), [tecov\(\)](#), [telcc\(\)](#), [temvn\(\)](#), [terec\(\)](#), [tesmp\(\)](#), [tetd\(\)](#), [tertools\(\)](#)

Examples

```
set.seed(123)
# (6 x 1) base forecasts vector (simulated), forecast horizon = 3
# and intermediate aggregation order k = 2 (max agg order = 4)
basek2 <- rnorm(3*2, 5)
# Same weights for different forecast horizons
fix_weights <- runif(4)
reco <- temo(base = basek2, order = 2, agg_order = 4, weights = fix_weights)

# Different weights for different forecast horizons
h_weights <- runif(4*3)
recoh <- temo(base = basek2, order = 2, agg_order = 4, weights = h_weights)
```

temvn

Temporal Gaussian Probabilistic Reconciliation

Description

This function performs temporal probabilistic forecast reconciliation assuming a multivariate normal base forecast distribution (Girolimetto et al., 2024) for a single time series using temporal hierarchies (Athanasopoulos et al., 2017).

Usage

```
temvn(base, agg_order, tew = "sum", comb = "ols", res = NULL,
      approach = "proj", comb_base = comb, reduce_form = FALSE, ...)
```

Arguments

base	A $(h(k^* + m) \times 1)$ numeric vector containing the base forecasts to be reconciled, ordered from lowest to highest frequency; m is the maximum aggregation order, k^* is the sum of a chosen subset of the $p - 1$ factors of m (excluding m itself) and h is the forecast horizon for the lowest frequency time series.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
comb	A string specifying the reconciliation method. For a complete list, see tecov .
res	A $(N(k^* + m) \times 1)$ optional numeric vector containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency. This vector is used to compute come covariance matrices.
approach	A string specifying the approach used to compute the reconciled forecasts. Options include: • "proj" (<i>default</i>): Projection approach according to Byron (1978, 1979). • "strc": Structural approach as proposed by Hyndman et al. (2011). • "proj_osqp": Numerical solution using osqp for projection approach. • "strc_osqp": Numerical solution using osqp for structural approach.
comb_base	A string specifying the base covariance matrix approach. For a complete list, see tecov . Default is the equal to comb.
reduce_form	A logical parameter indicating whether the function should return the full distribution (FALSE, <i>default</i>) or only the distribution corresponding to the high-frequency time series (TRUE).
...	Arguments passed on to tecov
mse	If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected.
shrink_fun	Shrinkage function of the covariance matrix, shrink_estim (<i>default</i>)

Value

A [distributional::dist_multivariate_normal](#) of reconciled forecasts, of class `foreco` (see [foreco-class](#)).

References

- Athanasopoulos, G., Hyndman, R.J., Kourentzes, N. and Petropoulos, F. (2017), Forecasting with Temporal Hierarchies, *European Journal of Operational Research*, 262, 1, 60-74. doi:10.1016/j.ejor.2017.02.046
- Byron, R.P. (1978), The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 141, 3, 359-367. doi:10.2307/2344807

Byron, R.P. (1979), Corrigenda: The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 142(3), 405. doi:[10.2307/2982515](https://doi.org/10.2307/2982515)

Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. doi:[10.1016/j.ijforecast.2023.10.003](https://doi.org/10.1016/j.ijforecast.2023.10.003)

Hyndman, R.J., Ahmed, R.A., Athanasopoulos, G. and Shang, H.L. (2011), Optimal combination forecasts for hierarchical time series, *Computational Statistics & Data Analysis*, 55, 9, 2579-2589. doi:[10.1016/j.csda.2011.03.006](https://doi.org/10.1016/j.csda.2011.03.006)

See Also

Probabilistic reconciliation: [csmvn\(\)](#), [cssmp\(\)](#), [ctmvn\(\)](#), [ctsmp\(\)](#), [tesmp\(\)](#)

Temporal framework: [teboot\(\)](#), [tebu\(\)](#), [tecov\(\)](#), [telcc\(\)](#), [temo\(\)](#), [terec\(\)](#), [tesmp\(\)](#), [tetd\(\)](#), [tertools\(\)](#)

Examples

```
set.seed(123)
# (7 x 1) base forecasts vector (simulated), m = 4
base <- rnorm(7*2, rep(c(20, 10, 5), 2*c(1, 2, 4)))
# (70 x 1) in-sample residuals vector (simulated)
res <- rnorm(70)

m <- 4 # from quarterly to annual temporal aggregation
reco_dist <- temvn(base = base, agg_order = m, comb = "wlsv", res = res)
```

teprojmat

Projection Matrix for Optimal Combination Temporal Reconciliation

Description

This function computes the projection or the mapping matrix $\mathbf{M}$ and $\mathbf{G}$, respectively, such that $\tilde{\mathbf{y}} = \mathbf{M}\hat{\mathbf{y}} = \mathbf{S}_{te}\mathbf{G}\hat{\mathbf{y}}$, where $\tilde{\mathbf{y}}$ is the vector of the reconciled forecasts, $\hat{\mathbf{y}}$ is the vector of the base forecasts, $\mathbf{S}_{te}$ is the temporal structural matrix, and $\mathbf{M} = \mathbf{S}_{te}\mathbf{G}$. For further information regarding on the structure of these matrices, refer to Girolimetto et al. (2023).

Usage

```
teprojmat(agg_order, comb = "ols", res = NULL, mat = "M", tew = "sum", ...)
```

Arguments

agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
comb	A string specifying the reconciliation method. For a complete list, see tecov .

res	A $(N(k^* + m) \times 1)$ optional numeric vector containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency. This vector is used to compute come covariance matrices.
mat	A string specifying which matrix to return: "M" (<i>default</i>) for M and "G" for G .
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
...	Arguments passed on to tecov
mse	If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected.
shrink_fun	Shrinkage function of the covariance matrix, shrink_estim (<i>default</i>)

Value

The projection matrix **M** (mat = "M") or the mapping matrix **G** (mat = "G").

References

Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. doi:10.1016/j.ijforecast.2023.10.003

See Also

Utilities: [aggts\(\)](#), [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [balance_hierarchy\(\)](#), [commat\(\)](#), [csprojmat\(\)](#), [cstools\(\)](#), [ctprojmat\(\)](#), [cttools\(\)](#), [df2aggmat\(\)](#), [lcmat\(\)](#), [res2matrix\(\)](#), [set_bounds\(\)](#), [shrink_estim\(\)](#), [shrink_oasd\(\)](#), [tetools\(\)](#), [unbalance_hierarchy\(\)](#)

Examples

```
# Temporal framework (annual-quarterly)
Mte <- teprojmat(agg_order = 4, comb = "ols")
Gte <- teprojmat(agg_order = 4, comb = "ols", mat = "G")
```

terec	<i>Optimal Combination Temporal Reconciliation</i>
-------	--

Description

This function performs forecast reconciliation for a single time series using temporal hierarchies (Athanasopoulos et al., 2017, Nystrup et al., 2020). The reconciled forecasts can be computed using either a projection approach (Byron, 1978, 1979) or the equivalent structural approach by Hyndman et al. (2011). Non-negative (Di Fonzo and Girolimetto, 2023) and immutable reconciled forecasts can be considered.

Usage

```
terec(base, agg_order, tew = "sum", comb = "ols", res = NULL,
      approach = "proj", nn = NULL, settings = NULL, bounds = NULL,
      immutable = NULL, ...)
```

Arguments

base	A $(h(k^* + m) \times 1)$ numeric vector containing the base forecasts to be reconciled, ordered from lowest to highest frequency; m is the maximum aggregation order, k^* is the sum of a chosen subset of the $p - 1$ factors of m (excluding m itself) and h is the forecast horizon for the lowest frequency time series.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
comb	A string specifying the reconciliation method. For a complete list, see tecov .
res	A $(N(k^* + m) \times 1)$ optional numeric vector containing the in-sample residuals or validation errors ordered from the lowest frequency to the highest frequency. This vector is used to compute come covariance matrices.
approach	A string specifying the approach used to compute the reconciled forecasts. Options include: "proj" (<i>default</i>): Projection approach according to Byron (1978, 1979). "strc": Structural approach as proposed by Hyndman et al. (2011). "proj_osqp": Numerical solution using osqp for projection approach. "strc_osqp": Numerical solution using osqp for structural approach.
nn	A string specifying the algorithm to compute non-negative forecasts: "osqp": quadratic programming optimization (osqp solver, Girolimetto 2025). "bpv": block principal pivoting algorithm (Wickramasuriya et al., 2020). "nfca": negative forecasts correction algorithm (Kourentzes and Athanassopoulos, 2021; Girolimetto 2025). "nnic": iterative non-negative reconciliation with immutable constraints (Girolimetto 2025). "sntz": heuristic "set-negative-to-zero" (Di Fonzo and Girolimetto, 2023; Girolimetto 2025).
settings	A list of control parameters. - nn = "osqp" An object of class <code>osqpSettings</code> specifying settings for the osqp solver. For details, refer to the osqp documentation (Stellato et al., 2020) - nn = "bpv" - ptype = "fixed": permutation method: "random" or "fixed" - par = 10: the number of full exchange rules that may be attempted - tol = <code>sqrt(.Machine\$double.eps)</code>: the tolerance criteria

	– <code>gtol = sqrt(.Machine\$double.eps)</code>: the gradient tolerance criteria – <code>itmax = 100</code>: the maximum number of algorithm iterations • <code>nn = "nfca"</code> and <code>nn = "nnic"</code> – <code>tol = sqrt(.Machine\$double.eps)</code>: the tolerance criteria – <code>itmax = 100</code>: the maximum number of algorithm iterations • <code>nn = "sntz"</code> – <code>type = "bu"</code>: the type of set-negative-to-zero heuristic: "bu" for bottom-up, "tdp" for top-down proportional, "tdsp" for top-down square proportional, "tdvw" for top-down variance weighted (the <code>res</code> param is used). See Girolimetto (2025) for details. – <code>tol = sqrt(.Machine\$double.eps)</code>: the tolerance identification of negative values
bounds	A matrix (see set_bounds) with 4 columns ($k, j, lower, upper$), such that • Column 1 represents the temporal aggregation order ($k = m, \dots, 1$). • Column 2 represents the temporal forecast horizon ($j = 1, \dots, m/k$). • Columns 3 and 4 indicates the <i>lower</i> and <i>upper</i> bounds, respectively.
immutable	A matrix with 2 columns (k, j), such that • Column 1 represents the temporal aggregation order ($k = m, \dots, 1$). • Column 2 represents the temporal forecast horizon ($j = 1, \dots, m/k$). For example, when working with a quarterly time series: • <code>t(c(4, 1))</code> - Fix the one step ahead annual forecast. • <code>t(c(1, 2))</code> - Fix the two step ahead quarterly forecast.
...	Arguments passed on to tecov <code>mse</code> If TRUE (<i>default</i>) the errors used to compute the covariance matrix are not mean-corrected. <code>shrink_fun</code> Shrinkage function of the covariance matrix, shrink_estim (<i>default</i>)

Value

An object of class `foreco` (see [foreco-class](#)) with a $(h(k^* + m) \times 1)$ numeric vector of temporal reconciled forecasts.

References

- Athanasopoulos, G., Hyndman, R.J., Kourentzes, N. and Petropoulos, F. (2017), Forecasting with Temporal Hierarchies, *European Journal of Operational Research*, 262, 1, 60-74. doi:10.1016/j.ejor.2017.02.046
- Byron, R.P. (1978), The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 141, 3, 359-367. doi:10.2307/2344807
- Byron, R.P. (1979), Corrigenda: The estimation of large social account matrices, *Journal of the Royal Statistical Society, Series A*, 142(3), 405. doi:10.2307/2982515
- Di Fonzo, T. and Girolimetto, D. (2023), Spatio-temporal reconciliation of solar forecasts, *Solar Energy*, 251, 13–29. doi:10.1016/j.solener.2023.01.003

Girolimetto, D. (2025), Non-negative forecast reconciliation: Optimal methods and operational solutions. *Forecasting*, 7(4), 64; doi:10.3390/forecast7040064

Hyndman, R.J., Ahmed, R.A., Athanasopoulos, G. and Shang, H.L. (2011), Optimal combination forecasts for hierarchical time series, *Computational Statistics & Data Analysis*, 55, 9, 2579-2589. doi:10.1016/j.csda.2011.03.006

Kourentzes, N. and Athanasopoulos, G. (2021) Elucidate structure in intermittent demand series. *European Journal of Operational Research*, 288, 141-152. doi:10.1016/j.ejor.2020.05.046

Nystrup, P., Lindström, E., Pinson, P. and Madsen, H. (2020), Temporal hierarchies with autocorrelation for load forecasting, *European Journal of Operational Research*, 280, 1, 876-888. doi:10.1016/j.ejor.2019.07.061

Stellato, B., Banjac, G., Goulart, P., Bemporad, A. and Boyd, S. (2020), OSQP: An Operator Splitting solver for Quadratic Programs, *Mathematical Programming Computation*, 12, 4, 637-672. doi:10.1007/s12532020001792

Wickramasuriya, S. L., Turlach, B. A., and Hyndman, R. J. (2020). Optimal non-negative forecast reconciliation. *Statistics and Computing*, 30(5), 1167–1182. doi:10.1007/s11222020099300

See Also

Regression-based reconciliation: `csrec()`, `ctrec()`

Temporal framework: `teboot()`, `tebu()`, `tecov()`, `telcc()`, `temo()`, `temvn()`, `tesmp()`, `tetd()`, `tetools()`

Examples

```
set.seed(123)
# (7 x 1) base forecasts vector (simulated), m = 4
base <- rnorm(7, rep(c(20, 10, 5), c(1, 2, 4)))
# (70 x 1) in-sample residuals vector (simulated)
res <- rnorm(70)

m <- 4 # from quarterly to annual temporal aggregation
reco <- terrec(base = base, agg_order = m, comb = "wlsv", res = res)

# Immutable reconciled forecast
# E.g. fix all the quarterly forecasts
imm_q <- expand.grid(k = 1, j = 1:4)
immreco <- terrec(base = base, agg_order = m, comb = "wlsv",
                  res = res, immutable = imm_q)

# Non negative reconciliation
base[7] <- -base[7] # Making negative one of the quarterly base forecasts
nnreco <- terrec(base = base, agg_order = m, comb = "wlsv",
                res = res, nn = "osqp")
summary(nnreco)
```

tesmp

*Temporal Probabilistic Reconciliation (Sample Approach)***Description**

This function performs temporal probabilistic forecast reconciliation using a sample-based approach (Girolimetto et al., 2024) for a single time series using temporal hierarchies (Athanasopoulos et al., 2017). Given a $(L \times h(k^* + m))$ matrix of simulated base forecast draws, `tesmp()` applies a chosen **FoReco** temporal reconciliation independently to each draw, producing a coherent sample distribution of reconciled forecasts across the temporal hierarchy. Typical choices for the reconciliation include optimal combination (`terec`) as well as top-down (`tetd`), middle-out (`temo`), bottom-up (`tebu`), and level-conditional (`telcc`) approaches.

Usage

```
tesmp(sample, agg_order, fun = terec, ...)
```

Arguments

sample	A $(L \times h(k^* + m))$ numeric matrix containing the base forecasts samples to be reconciled; m is the max aggregation order, k^* is the sum of (a subset of) $(p - 1)$ factors of m , excluding m , h is the forecast horizon for the lowest frequency time series, and L is the sample size.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
fun	A function performing the reconciliation, as implemented in FoReco .
...	Arguments passed on to fun

Value

A `distributional::dist_sample` of reconciled forecasts, of class `foreco` (see `foreco-class`).

References

Athanasopoulos, G., Hyndman, R.J., Kourentzes, N. and Petropoulos, F. (2017), Forecasting with Temporal Hierarchies, *European Journal of Operational Research*, 262, 1, 60-74. doi:10.1016/j.ejor.2017.02.046

Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. doi:10.1016/j.ijforecast.2023.10.003

See Also

Probabilistic reconciliation: `csmvn()`, `cssmp()`, `ctmvn()`, `ctsmv()`, `temvn()`
 Temporal framework: `teboot()`, `tebu()`, `tecov()`, `telcc()`, `temo()`, `temvn()`, `terec()`, `tetd()`, `tetools()`

Examples

```
set.seed(123)
m <- 4 # from quarterly to annual temporal aggregation

# (100 x 14) base forecasts sample matrix (simulated), m = 4, h = 2
sample <- t(sapply(1:100, function(x) {
  rnorm(14, rep(c(20, 10, 5), 2 * c(1, 2, 4)))
}))
# (70 x 1) in-sample residuals vector (simulated)
res <- rnorm(70)

# Top-down probabilistic reconciliation
reco_dist_td <- tetsmp(sample[,c(1:2)], drop = FALSE, agg_order = m,
  fun = tetd, weights = c(0.2, 0.5, 0.3, 0.3))

# Middle-out probabilistic reconciliation
reco_dist_mo <- tetsmp(sample[,c(3:6)], drop = FALSE, agg_order = m,
  fun = temo, weights = c(0.2, 0.5, 0.3, 0.3), order = 2)

# Bottom-up probabilistic reconciliation
reco_dist_bu <- tetsmp(sample[,c(1:6)], agg_order = m, fun = tebu)

# Level conditional coherent probabilistic reconciliation
reco_dist_lcc <- tetsmp(sample, agg_order = m, fun = telcc)

# Optimal cross-sectional probabilistic reconciliation
reco_dist_opt <- tetsmp(sample, agg_order = m, res = res, comb = "wlsv")
```

tetd

Temporal Top-down Reconciliation

Description

Top-down forecast reconciliation for a univariate time series, where the forecast of the most aggregated temporal level is disaggregated according to a proportional scheme (weights). Besides fulfilling any aggregation constraint, the top-down reconciled forecasts should respect two main properties:

- the top-level value remains unchanged;
- all the bottom time series reconciled forecasts are non-negative.

Usage

```
tetd(base, agg_order, weights, tew = "sum", normalize = TRUE)
```

Arguments

base	A $(hm \times 1)$ numeric vector containing the temporal aggregated base forecasts of order m ; m is the max aggregation order, and h is the forecast horizon for the lowest frequency time series.
agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
weights	A $(hm \times 1)$ numeric vector containing the proportions for the high-frequency time series; m is the max aggregation order, and h is the forecast horizon for the lowest frequency time series.
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
normalize	If TRUE (<i>default</i>), the weights will sum to 1.

Value

An object of class `foreco` (see [foreco-class](#)) with a $(h(k^* + m) \times 1)$ numeric vector of temporal reconciled forecasts.

See Also

Top-down reconciliation: [cstd\(\)](#), [cttd\(\)](#)

Temporal framework: [teboot\(\)](#), [tebu\(\)](#), [tecov\(\)](#), [telcc\(\)](#), [temo\(\)](#), [temvn\(\)](#), [terec\(\)](#), [tesmp\(\)](#), [tetools\(\)](#)

Examples

```
set.seed(123)
# (2 x 1) top base forecasts vector (simulated), forecast horizon = 2
topf <- rnorm(2, 10)
# Same weights for different forecast horizons
fix_weights <- runif(4)
reco <- tetd(base = topf, agg_order = 4, weights = fix_weights)

# Different weights for different forecast horizons
h_weights <- runif(4*2)
recoh <- tetd(base = topf, agg_order = 4, weights = h_weights)
```

Description

Some useful tools for forecast reconciliation through temporal hierarchies.

Usage

```
tertools(agg_order, fh = 1, tew = "sum", sparse = TRUE)
```

Arguments

agg_order	Highest available sampling frequency per seasonal cycle (max. order of temporal aggregation, m), or a vector representing a subset of p factors of m .
fh	Forecast horizon for the lowest frequency (most temporally aggregated) time series (<i>default</i> is 1).
tew	A string specifying the type of temporal aggregation. Options include: "sum" (simple summation, <i>default</i>), "avg" (average), "first" (first value of the period), and "last" (last value of the period).
sparse	Option to return sparse matrices (<i>default</i> is TRUE).

Value

A list with five elements:

dim	A vector containing information about the maximum aggregation order (m), the number of factor (p), the partial (ks) and total sum (kt) of factors.
set	The vector of the temporal aggregation orders (in decreasing order).
agg_mat	The temporal linear combination or aggregation matrix.
strc_mat	The temporal structural matrix.
cons_mat	The temporal zero constraints matrix.

See Also

Temporal framework: [teboot\(\)](#), [tebu\(\)](#), [tecov\(\)](#), [telcc\(\)](#), [temo\(\)](#), [temvn\(\)](#), [terec\(\)](#), [tesmp\(\)](#), [tetd\(\)](#)

Utilities: [aggts\(\)](#), [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [balance_hierarchy\(\)](#), [commat\(\)](#), [csprojmat\(\)](#), [cstools\(\)](#), [ctprojmat\(\)](#), [cttools\(\)](#), [df2aggmat\(\)](#), [lcmat\(\)](#), [res2matrix\(\)](#), [set_bounds\(\)](#), [shrink_estim\(\)](#), [shrink_oasd\(\)](#), [teprojmat\(\)](#), [unbalance_hierarchy\(\)](#)

Examples

```
# Temporal framework (quarterly data)
obj <- tertools(agg_order = 4, sparse = FALSE)
```

unbalance_hierarchy	<i>Aggregation Matrix of a Balanced Hierarchy in (Possibly) Unbalanced Form</i>
---------------------	---

Description

A hierarchy with L upper levels is said to be balanced if each variable at level l has at least one child at level $l + 1$. When this doesn't hold, the hierarchy is unbalanced. This function transforms an aggregation matrix of a balanced hierarchy into an aggregation matrix of an unbalanced one, by removing possible duplicated series.

Usage

```
unbalance_hierarchy(agg_mat, more_info = FALSE, sparse = TRUE)
```

Arguments

agg_mat	A $(n_a \times n_b)$ numeric matrix representing the cross-sectional aggregation matrix. It maps the n_b bottom-level (free) variables into the n_a upper (constrained) variables.
more_info	If TRUE, it returns only the aggregation matrix of the unbalanced hierarchy. <i>Default</i> is FALSE.
sparse	Option to return sparse matrices (<i>default</i> is TRUE).

Value

A list containing four elements (`more_info = TRUE`):

ubm	The aggregation matrix of the unbalanced hierarchy.
agg_mat	The input matrix.
idrm	The identification number of the duplicated variables (row numbers of the aggregation matrix <code>agg_mat</code>).
id	The identification number of each variable in the balanced hierarchy. It may contains duplicated values.

See Also

Utilities: [aggts\(\)](#), [as_ctmatrix\(\)](#), [as_tevector\(\)](#), [balance_hierarchy\(\)](#), [commat\(\)](#), [csprojmat\(\)](#), [cstools\(\)](#), [ctprojmat\(\)](#), [cttools\(\)](#), [df2aggmat\(\)](#), [lcmat\(\)](#), [res2matrix\(\)](#), [set_bounds\(\)](#), [shrink_estim\(\)](#), [shrink_oasd\(\)](#), [teprojmat\(\)](#), [tertools\(\)](#)

Examples

```
#      Balanced      ->      Unbalanced
#      T              T
#      |-----|      |-----|
#      A      B      A      |
#      |---|      |      |---|      |
#      AA      AB      BA      AA      AB      BA
A <- matrix(c(1, 1, 1,
              1, 1, 0,
              0, 0, 1), 3, byrow = TRUE)
obj <- unbalance_hierarchy(agg_mat = A)
obj
```

vndata

Australian Tourism Demand Dataset

Description

The Australian Tourism Demand dataset (Wickramasuriya et al. 2019) measures the number of nights Australians spent away from home. It includes 228 monthly observations of Visitor Nights (VNs) from January 1998 to December 2016, and has a cross-sectional grouped structure based on a geographic hierarchy crossed by purpose of travel. The geographic hierarchy comprises 7 states, 27 zones, and 76 regions, for a total of 111 nested geographic divisions. Six of these zones are each formed by a single region, resulting in 105 unique nodes in the hierarchy. The purpose of travel comprises four categories: holiday, visiting friends and relatives, business, and other. To avoid redundancies (Girolimetto et al. 2023), 24 nodes (6 zones are formed by a single region) are not considered, resulting in an unbalanced hierarchy of 525 (304 bottom and 221 upper time series) unique nodes instead of the theoretical 555 with duplicated nodes.

Usage

```
# 525 time series of the Australian Tourism Demand dataset
vndata

# aggregation matrix
vnaggmat
```

Format

vndata is a (228×525) ts object, corresponding to 525 time series of the Australian Tourism Demand dataset (1998:01-2016:12).

vnaggmat is the (221×304) aggregation matrix.

Source

<https://robjhyndman.com/publications/mint/>

References

- Girolimetto, D., Athanasopoulos, G., Di Fonzo, T. and Hyndman, R.J. (2024), Cross-temporal probabilistic forecast reconciliation: Methodological and practical issues. *International Journal of Forecasting*, 40, 3, 1134-1151. doi:[10.1016/j.ijforecast.2023.10.003](https://doi.org/10.1016/j.ijforecast.2023.10.003)
- Wickramasuriya, S.L., Athanasopoulos, G. and Hyndman, R.J. (2019), Optimal forecast reconciliation for hierarchical and grouped time series through trace minimization, *Journal of the American Statistical Association*, 114, 526, 804-819. doi:[10.1080/01621459.2018.1448825](https://doi.org/10.1080/01621459.2018.1448825)

Index

* Bootstrap samples

csboot, [6](#)
ctboot, [25](#)
teboot, [61](#)

* Framework: cross-sectional

csboot, [6](#)
csbu, [7](#)
cscov, [9](#)
cslcc, [10](#)
csmo, [14](#)
csmvn, [15](#)
csrec, [18](#)
cssmp, [21](#)
cstd, [23](#)
cstools, [24](#)

* Framework: cross-temporal

ctboot, [25](#)
ctbu, [27](#)
ctcov, [28](#)
ctlcc, [31](#)
ctmo, [34](#)
ctmvn, [36](#)
ctrec, [39](#)
ctsmp, [43](#)
cttd, [45](#)
cttools, [46](#)
iterec, [53](#)
tcsrec, [59](#)

* Framework: temporal

teboot, [61](#)
tebu, [63](#)
tecov, [64](#)
telcc, [66](#)
temo, [69](#)
temvn, [70](#)
terec, [73](#)
tesmp, [77](#)
tetd, [78](#)
tertools, [79](#)

* Reco: bottom-up

csbu, [7](#)
ctbu, [27](#)
tebu, [63](#)

* Reco: level conditional coherent

cslcc, [10](#)
ctlcc, [31](#)
telcc, [66](#)

* Reco: middle-out

csmo, [14](#)
ctmo, [34](#)
temo, [69](#)

* Reco: probabilistic

csmvn, [15](#)
cssmp, [21](#)
ctmvn, [36](#)
ctsmp, [43](#)
temvn, [70](#)
tesmp, [77](#)

* Reco: regression-based

csrec, [18](#)
ctrec, [39](#)
terec, [73](#)

* Reco: top-down

cstd, [23](#)
cttd, [45](#)
tetd, [78](#)

* Utilities

aggts, [3](#)
balance_hierarchy, [4](#)
csprojmat, [17](#)
cstools, [24](#)
ctprojmat, [38](#)
cttools, [46](#)
df2aggmat, [47](#)
lcmat, [54](#)
set_bounds, [56](#)
shrink_estim, [57](#)
shrink_oasd, [58](#)

- teprojmat, 72
- tetools, 79
- unbalance_hierarchy, 81
- * **datasets**
 - itagdp, 52
 - vndata, 82
- * **package**
 - FoReco-package, 3
- aggts, 3, 5, 18, 25, 39, 47, 48, 55, 56, 58, 59, 73, 80, 81
- as_ctmatrix, 4, 5, 18, 25, 39, 47, 48, 55, 56, 58, 59, 73, 80, 81
- as_tevector, 4, 5, 18, 25, 39, 47, 48, 55, 56, 58, 59, 73, 80, 81
- balance_hierarchy, 4, 4, 18, 25, 39, 47, 48, 55, 56, 58, 59, 73, 80, 81
- commat, 4, 5, 18, 25, 39, 47, 48, 55, 56, 58, 59, 73, 80, 81
- components.foreco (foreco-class), 49
- csboot, 6, 8, 10, 13, 15, 16, 21, 22, 24–26, 62
- csbu, 6, 7, 10, 13–16, 21, 22, 24, 25, 28, 63
- cscov, 6, 8, 9, 11–13, 15–17, 19–22, 24, 25
- csfcc, 5, 6, 8, 10, 10, 15, 16, 21, 22, 24, 25, 33, 68
- csmo, 6, 8, 10, 13, 14, 16, 21, 22, 24, 25, 35, 70
- csmvn, 6, 8, 10, 13, 15, 15, 21, 22, 24, 25, 37, 44, 72, 77
- csprojmat, 4, 5, 17, 25, 39, 47, 48, 55, 56, 58, 59, 73, 80, 81
- csrec, 6, 8, 10, 13, 15, 16, 18, 21, 22, 24, 25, 42, 53, 56, 60, 76
- cssmp, 6, 8, 10, 13, 15, 16, 21, 21, 24, 25, 37, 44, 72, 77
- cssmp(), 21
- cstd, 6, 8, 10, 13–16, 21, 22, 23, 25, 46, 79
- cstools, 4–6, 8, 10, 13, 15, 16, 18, 21, 22, 24, 24, 39, 47, 48, 55, 56, 58, 59, 73, 80, 81
- cstrec, 59
- cstrec (tcsrec), 59
- ctboot, 6, 25, 28, 30, 33, 35, 37, 42, 44, 46, 47, 54, 60, 62
- ctbu, 8, 26, 27, 30, 33–35, 37, 42–44, 46, 47, 54, 60, 63
- ctcov, 26, 28, 28, 31–33, 35–42, 44, 46, 47, 54, 60
- ctlcc, 13, 26, 28, 30, 31, 35, 37, 42–44, 46, 47, 54, 60, 68
- ctmo, 15, 26, 28, 30, 33, 34, 37, 42–44, 46, 47, 54, 60, 70
- ctmvn, 16, 22, 26, 28, 30, 33, 35, 36, 42, 44, 46, 47, 54, 60, 72, 77
- ctprojmat, 4, 5, 18, 25, 38, 47, 48, 55, 56, 58, 59, 73, 80, 81
- ctrec, 21, 26, 28, 30, 33, 35, 37, 39, 43, 44, 46, 47, 54, 56, 60, 76
- ctsmp, 16, 22, 26, 28, 30, 33, 35, 37, 42, 43, 46, 47, 54, 60, 72, 77
- ctsmp(), 43
- cttd, 24, 26, 28, 30, 33–35, 37, 42–44, 45, 47, 54, 60, 79
- cttools, 4, 5, 18, 25, 26, 28, 30, 33, 35, 37, 39, 42, 44, 46, 46, 48, 54–56, 58–60, 73, 80, 81
- df2aggmat, 4, 5, 18, 25, 39, 47, 47, 55, 56, 58, 59, 73, 80, 81
- distributional::dist_multivariate_normal, 16, 37, 71
- distributional::dist_sample, 22, 44, 77
- drop_foreco_class (foreco-class), 49
- expside (itagdp), 52
- FoReco (FoReco-package), 3
- foreco (foreco-class), 49
- foreco-class, 8, 12, 14, 16, 20, 22, 23, 28, 33, 35, 37, 41, 44, 45, 49, 53, 60, 63, 67, 70, 71, 75, 77, 79
- FoReco-package, 3
- gdpconsmat (itagdp), 52
- incside (itagdp), 52
- itagdp, 52
- iterec, 26, 28, 30, 33, 35, 37, 42, 44, 46, 47, 53, 60
- lcmat, 4, 5, 18, 25, 39, 47, 48, 54, 56, 58, 59, 73, 80, 81
- new_foreco_class (foreco-class), 49
- outside (itagdp), 52
- plot.foreco (foreco-class), 49

print.foreco (foreco-class), 49
 print.summary_foreco (foreco-class), 49

 res2matrix, 4, 5, 18, 25, 39, 47, 48, 55, 56,
 58, 59, 73, 80, 81

 set_bounds, 4, 5, 18, 20, 25, 39, 41, 47, 48,
 55, 56, 58, 59, 73, 75, 80, 81
 shrink_estim, 4, 5, 9, 12, 16–18, 20, 25, 29,
 32, 37, 39, 41, 47, 48, 55, 56, 57, 59,
 65, 67, 71, 73, 75, 80, 81
 shrink_oasd, 4, 5, 18, 25, 39, 47, 48, 55, 56,
 58, 58, 73, 80, 81
 summary.foreco (foreco-class), 49

 tcsrec, 26, 28, 30, 33, 35, 37, 42, 44, 46, 47,
 54, 59, 59
 teboot, 6, 26, 61, 63, 65, 68, 70, 72, 76, 77,
 79, 80
 tebu, 8, 28, 62, 63, 65, 68–70, 72, 76, 77, 79,
 80
 tecov, 62, 63, 64, 66–68, 70–77, 79, 80
 telcc, 13, 33, 62, 63, 65, 66, 70, 72, 76, 77,
 79, 80
 temo, 15, 35, 62, 63, 65, 68, 69, 72, 76, 77, 79,
 80
 temvn, 16, 22, 37, 44, 62, 63, 65, 68, 70, 70,
 76, 77, 79, 80
 teproimat, 4, 5, 18, 25, 39, 47, 48, 55, 56, 58,
 59, 72, 80, 81
 terec, 21, 42, 53, 56, 60, 62, 63, 65, 68, 70,
 72, 73, 77, 79, 80
 tesmp, 16, 22, 37, 44, 62, 63, 65, 68, 70, 72,
 76, 77, 79, 80
 tesmp(), 77
 tetd, 24, 46, 62, 63, 65, 68–70, 72, 76, 77, 78,
 80
 tetools, 4, 5, 18, 25, 39, 47, 48, 55, 56, 58,
 59, 62, 63, 65, 68, 70, 72, 73, 76, 77,
 79, 79, 81

 unbalance_hierarchy, 4, 5, 18, 25, 39, 47,
 48, 55, 56, 58, 59, 73, 80, 81

 vnaggmat (vnadata), 82
 vnadata, 82